

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

BG02-S000-OAB
Version 8.1

SolvSeal UniQuickPrimer
Revision date 6 Jun 2025

Print date 6 Jun 2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

BG02-S000-OAB SolvSeal UniQuickPrimer
UFI: K6AJ-20H9-C00C-SQAN

1.2 Relevant identified uses of the substance or mixture and uses advised against

paint and/or paint-related material

Relevant identified uses

Reserved for industrial and professional use.

Uses advised against

Do not use for injecting or spraying.

1.3 Details of the supplier of the safety data sheet

Supplier

Berger-Seidle GmbH
Maybachstr. 2 Telephone: +49 6359 8005-0
67269 Grünstadt E-mail: info@berger-seidle.de
Germany Website: www.berger-seidle.de

Department responsible for information

E-mail (competent person) Sicherheitsdaten@berger-seidle.de

1.4 Emergency telephone number

Emergency telephone number +49 700 24112112
24 hr. emergency phone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 Narcotic effects H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS02 GHS07

Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.

Hazard components for labelling

* isopropanol; isopropyl alcohol; propan-2-ol

Supplemental hazard information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

BG02-S000-OAB
Version 8.1

SolvSeal UniQuickPrimer
Revision date 6 Jun 2025

Print date 6 Jun 2025

not applicable

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

PVB = Polyvinylbutyral

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
* 64-17-5 200-578-6 603-002-00-5	ethanol; ethyl alcohol 01-2119457610-43-XXXX Flam. Liq. 2 H225 / Eye Irrit. 2 H319 Specific concentration limit (SCL) Eye Irrit. 2 H319: >= 50,00	50,0 < 70,0
* 67-63-0 200-661-7 603-117-00-0	isopropanol; isopropyl alcohol; propan-2-ol 01-2119457558-25-XXXX Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	12,5 < 15,0
* 107-98-2 203-539-1 603-064-00-3	1-methoxy-2-propanol; monopropylene glycol methyl ether 01-2119457435-35-XXXX Flam. Liq. 3 H226 / STOT SE 3 H336 Substance with a common (EC) occupational exposure limit value.	12,5 < 15,0

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

In case of irregular breathing or respiratory arrest provide artificial respiration. Remove casualty to fresh air and keep warm and at rest.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

BG02-S000-OAB
Version 8.1

SolvSeal UniQuickPrimer
Revision date 6 Jun 2025

Print date 6 Jun 2025

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Personal protection equipment: see section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSivO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class LGK3 - Flammable liquids

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Store in a well-ventilated and dry room at temperatures between 5 °C and 25 °C.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

BG02-S000-OAB
Version 8.1

SolvSeal UniQuickPrimer
Revision date 6 Jun 2025

Print date 6 Jun 2025

Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	WEL	375 / 560 (-) mg/m ³ (may be absorbed through the skin)
* 64-17-5	ethanol; ethyl alcohol	WEL	1,920 / - (-) mg/m ³
* 67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	WEL	999 / 1,250 (-) mg/m ³

Additional information

Long-term: Long-term occupational exposure limit value
short-term: short-term occupational exposure limit value

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	Long-term – inhalation, systemic effects	369 mg/m ³
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	Acute - inhalation, local effects	553.5 mg/m ³
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	Long-term - dermal, systemic effects	183 mg/kg bw/day
* 64-17-5	ethanol; ethyl alcohol	Long-term – inhalation, systemic effects	380 mg/m ³
* 67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	Long-term – inhalation, systemic effects	500 mg/m ³
* 67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	Long-term - dermal, systemic effects	888 mg/kg bw/day

DNEL Consumer

CAS No.	Substance name	DNEL type	DNEL value
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	Long-term – inhalation, systemic effects	43.9 mg/m ³
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	Long-term - dermal, systemic effects	78 mg/kg bw/day
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	Long-term - oral, systemic effects	33 mg/kg bw/day
* 64-17-5	ethanol; ethyl alcohol	Long-term – inhalation, systemic effects	114 mg/m ³
* 67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	Long-term – inhalation, systemic effects	89 mg/m ³
* 67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	Acute - inhalation, systemic effects	178
* 67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	Long-term - dermal, systemic effects	319 mg/kg bw/day
* 67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	Long-term - oral, systemic effects	26 mg/kg bw/day

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	aquatic, intermittent release	100 mg/L
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	aquatic, marine water	1 mg/L
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	sewage treatment plant	100 mg/L
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	sediment, freshwater	52.3 mg/kg sediment dw
* 107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	sediment, marine water	5.2 mg/kg sediment dw

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

BG02-S000-OAB
Version 8.1

SolvSeal UniQuickPrimer
Revision date 6 Jun 2025

Print date 6 Jun 2025

*	64-17-5	ethanol; ethyl alcohol	aquatic, intermittent release	2.75 mg/L
*	64-17-5	ethanol; ethyl alcohol	aquatic, marine water	0.79 mg/L
*	64-17-5	ethanol; ethyl alcohol	sewage treatment plant	580 mg/L
*	64-17-5	ethanol; ethyl alcohol	sediment, freshwater	3.6 mg/kg sediment dw
*	64-17-5	ethanol; ethyl alcohol	sediment, marine water	2.9
*	67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	PNEC soil, freshwater	28 mg/kg
*	67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	PNEC sediment, marine water	552 mg/kg
*	67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	PNEC sediment, freshwater	552 mg/kg
*	67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	PNEC Secondary Poisoning	160 mg/kg
*	67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	PNEC aquatic, marine water	140.9 mg/L
*	67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	PNEC aquatic, freshwater	140.9 mg/L
*	67-63-0	isopropanol; isopropyl alcohol; propan-2-ol	PNEC sewage treatment plant (STP)	2,251 mg/L

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material ≥ 0.4 mm

Breakthrough time ≥ 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Anti-static clothing including shoes are recommended.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	colourless
Odour	characteristic
pH at 20 °C	not applicable
Melting point/freezing point	-89.5 °C
	Source: isopropanol; isopropyl alcohol; propan-2-ol
Initial boiling point and boiling range	78.5 °C
	Source: ethanol; ethyl alcohol
Flash point	16 °C
flammability	Highly flammable liquid and vapour.
Lower explosion limit at 20°C	1.5 Vol-%
	Source: 1-methoxy-2-propanol; monopropylene glycol methyl ether

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

BG02-S000-OAB
Version 8.1

SolvSeal UniQuickPrimer
Revision date 6 Jun 2025

Print date 6 Jun 2025

Upper explosion limit at 20°C	15 Vol-% Source: ethanol; ethyl alcohol
Vapour pressure at 20°C	3.075 mbar
Relative vapour density	not applicable
Density at 20 °C	0.83 kg/l
Water solubility at 20°C	partially soluble
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	287 °C Source: 1-methoxy-2-propanol; monopropylene glycol methyl ether
Decomposition temperature	not determined
Viscosity at 20 °C	135 mm²/s
particle characteristics	not applicable

9.2 Other information

Solid content	9.6 %
solvent content	90.4 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

BG02-S000-OAB
Version 8.1

SolvSeal UniQuickPrimer
Revision date 6 Jun 2025

Print date 6 Jun 2025

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

* **isopropanol; isopropyl alcohol; propan-2-ol**

Biodegradation = 2.32 %

Biodegradation = 62 %

12.3 Bioaccumulative potential

isopropanol; isopropyl alcohol; propan-2-ol

* Partition coefficient: n-octanol/water = 0.16

Partition coefficient: n-octanol/water = -0.31 (ethanol; ethyl alcohol)

* Partition coefficient: n-octanol/water = 0.05 (isopropanol; isopropyl alcohol; propan-2-ol)

* Partition coefficient: n-octanol/water = -0.44 (1-methoxy-2-propanol; monopropylene glycol methyl ether)

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080111* - Waste paint and varnish containing organic solvents or other dangerous substances

* Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number or ID number

UN 1263

14.2 UN proper shipping name

Land transport (ADR/RID)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

BG02-S000-OAB
Version 8.1

SolvSeal UniQuickPrimer
Revision date 6 Jun 2025

Print date 6 Jun 2025

* PAINT

Sea transport (IMDG)

* PAINT

Air transport (ICAO-TI / IATA-DGR)

* PAINT

14.3 Transport hazard class(es)

Land transport (ADR/RID)	3
Sea transport (IMDG)	3
Air transport (ICAO-TI / IATA-DGR)	3

14.4 Packing group

* Land transport (ADR/RID)	II
* Sea transport (IMDG)	II
* Air transport (ICAO-TI / IATA-DGR)	II

14.5 Environmental hazards

Land transport (ADR/RID)	not applicable
Sea transport (IMDG)	not applicable

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

Tunnel restriction code: D/E

- * Limited quantity (LQ): 5 l
- Hazard identification number (Kemler No.): 33

Sea transport (IMDG)

- * EmS-No.: F-E, S-E
- Limited quantity (LQ): 5 l

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 03, 40

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 749 g/l

- * **Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**

- * VOC limit value: 2004/42/IIA(h): 750 g/l (2010)

- * Maximum VOC content of the product in a ready to use condition: 749 g/L. This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

- * This product is not classified according to Directive 2012/18/EU.

National regulations

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

BG02-S000-0AB
Version 8.1

SolvSeal UniQuickPrimer
Revision date 6 Jun 2025

Print date 6 Jun 2025

Observe in addition any national regulations!

Substance/product listed in the following inventories

Australian Inventory of Chemical Substances (AICS) - AU

Domestic Substances List (DSL) - CA

U.S. Toxic Substances Control Act (TSCA) - US

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2 On basis of test data.

Eye Irrit. 2 Calculation method.

STOT SE 3 Narcotic effects Calculation method.

Key literature references and sources for data

Data arise from reference works and literature.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

EC: European Community

EN: European Standard

EU/EEA: European Economic Area

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

:

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.