

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

YP06-8017-0AL
Version 2.0

BergerBond ColorAdd P
Revision date 23 Jun 2025

Print date 23 Jun 2025

Description

Pigmentpaste

Hazardous ingredients

*

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
34590-94-8 252-104-2 -	(2-methoxymethylethoxy)propanol 01-2119450011-60-XXXX Substance with a common (EC) occupational exposure limit value.	15,0 < 20,0
64742-95-6 918-668-5 649-356-00-4	Hydrocarbons, C9, aromatics 01-2119455851-35-XXXX Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H335 / STOT SE 3 H336 / Aquatic Chronic 2 H411	8,00 < 10,0
- - -	Salt of acidic polymer Skin Irrit. 2 H315 / Eye Irrit. 2 H319	3,00 < 5,00
108-65-6 203-603-9 607-195-00-7	2-methoxy-1-methylethyl acetate 01-2119475791-29-XXXX Flam. Liq. 3 H226 / STOT SE 3 H336 Substance with a common (EC) occupational exposure limit value.	2,00 < 2,50
54839-24-6 259-370-9 603-177-00-8	2-ethoxy-1-methylethyl acetate 01-2119475116-39-XXXX Flam. Liq. 3 H226 / STOT SE 3 H336	1,00 < 2,00
246538-78-3 920-901-0 -	Hydrocarbons, C11-C13, isoalkanes, <2% aromatics 01-2119456810-40-XXXX Asp. Tox. 1 H304 / EUH066 ATE (dermal): > 3.16 mL/kg	1,00 < 2,00
123-86-4 204-658-1 607-025-00-1	N-butyl acetate 01-2119485493-29-XXXX Flam. Liq. 3 H226 / STOT SE 3 H336 / EUH066 Substance with a common (EC) occupational exposure limit value.	1,00 < 2,00

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

In case of irregular breathing or respiratory arrest provide artificial respiration. Remove casualty to fresh air and keep warm and at rest.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

YP06-8017-0AL
Version 2.0

BergerBond ColorAdd P
Revision date 23 Jun 2025

Print date 23 Jun 2025

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Personal protection equipment: see section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class LGK10 - Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Store in a well-ventilated and dry room at temperatures between 5 °C and 25 °C.

7.3 Specific end use(s)

Observe technical data sheet.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

YP06-8017-0AL
Version 2.0

BergerBond ColorAdd P
Revision date 23 Jun 2025

Print date 23 Jun 2025

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
34590-94-8	(2-methoxymethylethoxy)propanol	WEL	308 / - (-) mg/m ³ (may be absorbed through the skin)
108-65-6	2-methoxy-1-methylethyl acetate	WEL	274 / 548 (-) mg/m ³ (may be absorbed through the skin)
7727-43-7	Barium sulfate	WEL	10 / - (-) mg/m ³ (inhalable fraction)
7727-43-7	Barium sulfate	WEL	4 / - (-) mg/m ³ (respirable fraction)
1333-86-4	Carbon black	WEL	3.5 / 7 (-) mg/m ³
100-41-4	Ethylbenzen	WEL	441 / 552 (-) mg/m ³ (may be absorbed through the skin)
13463-67-7	Titanium dioxide	WEL	10 / - (-) mg/m ³ (inhalable fraction)
13463-67-7	Titanium dioxide	WEL	4 / - (-) mg/m ³ (respirable fraction)

Additional information

Long-term: Long-term occupational exposure limit value
short-term: short-term occupational exposure limit value

Biological limit values

No data available

DNEL worker

	CAS No.	Substance name	DNEL type	DNEL value
*	34590-94-8	(2-methoxymethylethoxy)propanol	Long-term – inhalation, systemic effects	308 mg/m ³
*	34590-94-8	(2-methoxymethylethoxy)propanol	Long-term - dermal, systemic effects	283 mg/kg bw/day
	54839-24-6	2-ethoxy-1-methylethyl acetate	Long-term – inhalation, systemic effects	152 mg/m ³
	54839-24-6	2-ethoxy-1-methylethyl acetate	Long-term - dermal, systemic effects	103 mg/kg bw/day
	108-65-6	2-methoxy-1-methylethyl acetate	Long-term – inhalation, systemic effects	275 mg/m ³
	108-65-6	2-methoxy-1-methylethyl acetate	Acute - inhalation, local effects	550 mg/m ³
	108-65-6	2-methoxy-1-methylethyl acetate	Long-term - dermal, systemic effects	796 mg/kg bw/day
	64742-95-6	Hydrocarbons, C9, aromatics	DNEL long-term dermal (systemic)	12.5 mg/kg
	64742-95-6	Hydrocarbons, C9, aromatics	DNEL long-term inhalative (systemic)	151 mg/m ³
	123-86-4	N-butyl acetate	Long-term – inhalation, systemic effects	48 mg/m ³
	123-86-4	N-butyl acetate	Long-term - dermal, systemic effects	7 mg/kg bw/day

DNEL Consumer

	CAS No.	Substance name	DNEL type	DNEL value
*	34590-94-8	(2-methoxymethylethoxy)propanol	Long-term – inhalation,	37.2 mg/m ³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

YP06-8017-0AL
Version 2.0

BergerBond ColorAdd P
Revision date 23 Jun 2025

Print date 23 Jun 2025

		systemic effects	
*	34590-94-8	(2-methoxymethylethoxy)propanol	Long-term - dermal, systemic effects
			121 mg/kg bw/day
*	34590-94-8	(2-methoxymethylethoxy)propanol	Long-term - oral, systemic effects
			36 mg/kg bw/day
	54839-24-6	2-ethoxy-1-methylethyl acetate	Long-term – inhalation, systemic effects
			181 mg/m³
	54839-24-6	2-ethoxy-1-methylethyl acetate	Acute - inhalation, systemic effects
			1,420
	54839-24-6	2-ethoxy-1-methylethyl acetate	Long-term - dermal, systemic effects
			62 mg/kg bw/day
	54839-24-6	2-ethoxy-1-methylethyl acetate	Long-term - oral, systemic effects
			13.1 mg/kg bw/day
	108-65-6	2-methoxy-1-methylethyl acetate	Long-term – inhalation, systemic effects
			33 mg/m³
	108-65-6	2-methoxy-1-methylethyl acetate	Long-term – inhalation, local effects
			33 mg/m³
	108-65-6	2-methoxy-1-methylethyl acetate	Long-term - dermal, systemic effects
			320 mg/kg bw/day
	108-65-6	2-methoxy-1-methylethyl acetate	Long-term - oral, systemic effects
			36 mg/kg bw/day
	64742-95-6	Hydrocarbons, C9, aromatics	DNEL long-term dermal (systemic)
			7.5 mg/kg
	64742-95-6	Hydrocarbons, C9, aromatics	DNEL long-term inhalative (systemic)
			32 mg/m³
	123-86-4	N-butyl acetate	Long-term – inhalation, systemic effects
			12 mg/m³
	123-86-4	N-butyl acetate	Long-term - dermal, systemic effects
			3.4 mg/kg bw/day
	123-86-4	N-butyl acetate	Long-term - oral, systemic effects
			3.4 mg/kg bw/day

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
*	34590-94-8	(2-methoxymethylethoxy)propanol	aquatic, intermittent release
			190 mg/L
*	34590-94-8	(2-methoxymethylethoxy)propanol	aquatic, marine water
			1.9 mg/L
*	34590-94-8	(2-methoxymethylethoxy)propanol	sewage treatment plant
			4,168 mg/L
*	34590-94-8	(2-methoxymethylethoxy)propanol	sediment, freshwater
			70.2 mg/kg sediment dw
*	34590-94-8	(2-methoxymethylethoxy)propanol	sediment, marine water
			7.02 mg/kg sediment dw
	54839-24-6	2-ethoxy-1-methylethyl acetate	aquatic, intermittent release
			2 mg/L
	54839-24-6	2-ethoxy-1-methylethyl acetate	aquatic, marine water
			0.2 mg/L
	54839-24-6	2-ethoxy-1-methylethyl acetate	sewage treatment plant
			62.5 mg/L
	54839-24-6	2-ethoxy-1-methylethyl acetate	sediment, freshwater
			8.2 mg/kg sediment dw
	54839-24-6	2-ethoxy-1-methylethyl acetate	sediment, marine water
			0.82 mg/kg sediment dw
	108-65-6	2-methoxy-1-methylethyl acetate	aquatic, intermittent release
			6.35 mg/L
	108-65-6	2-methoxy-1-methylethyl acetate	aquatic, marine water
			0.064 mg/L
	108-65-6	2-methoxy-1-methylethyl acetate	sewage treatment plant
			100 mg/L
	108-65-6	2-methoxy-1-methylethyl acetate	sediment, freshwater
			3.29 mg/kg sediment dw
	108-65-6	2-methoxy-1-methylethyl acetate	sediment, marine water
			0.329 mg/kg sediment dw
	123-86-4	N-butyl acetate	aquatic, intermittent release
			0.36 mg/L
	123-86-4	N-butyl acetate	aquatic, marine water
			0.018 mg/L
	123-86-4	N-butyl acetate	sewage treatment plant
			35.6 mg/L
	123-86-4	N-butyl acetate	sediment, freshwater
			0.981 mg/kg sediment dw
	123-86-4	N-butyl acetate	sediment, marine water
			0.098 mg/kg sediment dw

8.2 Exposure controls

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

YP06-8017-0AL
Version 2.0

BergerBond ColorAdd P
Revision date 23 Jun 2025

Print date 23 Jun 2025

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material ≥ 0.4 mm

Breakthrough time ≥ 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Anti-static clothing including shoes are recommended.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	brown
Odour	characteristic
pH at 20 °C	not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥ 124 °C Source: N-butyl acetate
Flash point	> 61 °C
flammability	not applicable
Lower explosion limit at 20°C	0.6 Vol-% Source: Hydrocarbons, C11-C13, isoalkanes, <2% aromatics
Upper explosion limit at 20°C	14 Vol-% Source: (2-methoxymethylethoxy)propanol
Vapour pressure at 20°C	2.452 mbar
Relative vapour density	not applicable
Density at 20 °C	1.36 kg/l
Water solubility at 20°C	partially soluble
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	> 200 °C Source: Hydrocarbons, C11-C13, isoalkanes, <2% aromatics
Decomposition temperature	not determined
Viscosity at 20 °C	135 mm ² /s
particle characteristics	not applicable

9.2 Other information

Solid content	66.4 %
---------------	--------

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

YP06-8017-0AL
Version 2.0

BergerBond ColorAdd P
Revision date 23 Jun 2025

Print date 23 Jun 2025

solvent content

33.7 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics

LD50: dermal > 3.16 mL/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

YP06-8017-0AL
Version 2.0

BergerBond ColorAdd P
Revision date 23 Jun 2025

Print date 23 Jun 2025

Harmful to aquatic life with long lasting effects.

Acute (short-term) fish toxicity

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics

LL50: > 1,000 mg/L (96 h)

Acute (short-term) toxicity to algae and cyanobacteria

EL50: > 1,000 mg/L (72 h)

NOELR: 1,000 mg/L (72 h)

Acute (short-term) toxicity to aquatic invertebrates

LL50: > 1,000 mg/L (96 h)

NOELR: 1,000 mg/L (96 h)

Chronic (long-term) fish toxicity

(Oncorhynchus mykiss (Rainbow trout)):

Chronic (long-term) toxicity to aquatic invertebrate

NOELR: (Daphnia magna (Big water flea)): 1 mg/L (21 d)

12.2 Persistence and degradability

* **(2-methoxymethylethoxy)propanol**

Biodegradation = 75 % (28 d)

* Biodegradation = 93 % (13 d)

2-ethoxy-1-methylethyl acetate

Biodegradation = 100 % (28 d)

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics

Biodegradation = 31.3 % (28 d)

12.3 Bioaccumulative potential

* **(2-methoxymethylethoxy)propanol**

Partition coefficient: n-octanol/water = 1.01

* **N-butyl acetate**

Partition coefficient: n-octanol/water = 1.81

Partition coefficient: n-octanol/water = 0.43 (2-methoxy-1-methylethyl acetate)

* Partition coefficient: n-octanol/water = 0.35 ((2-methoxymethylethoxy)propanol)

Partition coefficient: n-octanol/water >= 1.99 (Hydrocarbons, C11-C13, isoalkanes, <2% aromatics)

Partition coefficient: n-octanol/water = 1.85 (N-butyl acetate)

* Partition coefficient: n-octanol/water = 0.76 (2-ethoxy-1-methylethyl acetate)

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080111* - Waste paint and varnish containing organic solvents or other dangerous substances

* Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Other disposal recommendations

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

YP06-8017-0AL
Version 2.0

BergerBond ColorAdd P
Revision date 23 Jun 2025

Print date 23 Jun 2025

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number or ID number

not applicable

14.2 UN proper shipping name

Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

not applicable

14.4 Packing group

not applicable

14.5 Environmental hazards

Land transport (ADR/RID)

not applicable

Sea transport (IMDG)

not applicable

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

not applicable

Sea transport (IMDG)

not applicable

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 03, 40

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 457 g/l

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

YP06-8017-0AL
Version 2.0

BergerBond ColorAdd P
Revision date 23 Jun 2025

Print date 23 Jun 2025

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 Calculation method.

Key literature references and sources for data

Data arise from reference works and literature.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

EC: European Community

EN: European Standard

EU/EEA: European Economic Area

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

:

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.