

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) KG404B1ADX10
Trade name/designation Classic BaseOil COLOR
Violett/Violet
abZ-Nr. Z-157.10-47

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

paint and/or paint related material
Reserved for industrial and professional use.

Uses advised against:

Do not use for injecting or spraying.

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Berger-Seidle GmbH
Parkettlacke - Klebstoffe - Bauchemie Telephone: +49 6359 / 8005-0
Maybachstraße 2 Telefax: +49 6359 / 8005-170
67269 Grünstadt
Germany

Department responsible for information:

Laboratory
E-mail Sicherheitsdaten@berger-seidle.de

1.4. Emergency telephone number

24-hour emergency number: +49 700 24112112
(BLG)
24-hour emergency number in side USA: +1 872 5888271 or +11 49 700 24112112 (BLG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Hazard statements

not applicable

Precautionary statements

not applicable

Hazard components for labelling

not applicable

Supplemental hazard information

EUH208 Contains phthalic anhydride. May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3. Other hazards

Spontaneous ignition possible through autoxidation of cloths soaked in the product. (The same applies to dust and other paint-soaked items). The product itself is not self ignitive.

Other information

Read label before use. If medical advice is needed, have product container or label at hand. Keep out of reach of children.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 2 / 10

Description

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
918-167-1	01-2119472146-39-XXXX Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Flam. Liq. 3 H226 / Asp. Tox. 1 H304	7,5 - 10
265-199-0 64742-95-6 649-356-00-4	01-2119455851-35-XXXX Hydrocarbons, C9, aromatics STOT SE 3 H335 / STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 3 H226	1 - 2,5
252-104-2 34590-94-8	01-2119450011-60-XXXX (2-methoxymethylethoxy)propanol Substance with a common (EC) occupational exposure limit value.	1 - 2,5
203-603-9 108-65-6 607-195-00-7	01-2119475791-29-XXXX 2-methoxy-1-methylethyl acetate Flam. Liq. 3 H226	1 - 2,5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 3 / 10

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

Hydrocarbons, C9, aromatics

Index No. 649-356-00-4 / EC No. 265-199-0 / CAS No. 64742-95-6

WEL, TWA: 500 mg/m³

Remark: (Aromatics)

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

WEL, TWA: 308 mg/m³; 50 ppm

Remark: (may be absorbed through the skin)

2-methoxy-1-methylethyl acetate

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 4 / 10

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

WEL, TWA: 274 mg/m³; 50 ppm

WEL, STEL: 548 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

DNEL long-term dermal (systemic), Workers: 153,5 mg/kg

DNEL long-term inhalative (systemic), Workers: 275 mg/m³

DNEL long-term oral (repeated), Consumer: 1,67 mg/kg

DNEL long-term dermal (systemic), Consumer: 54,8 mg/kg

DNEL long-term inhalative (systemic), Consumer: 33 mg/m³

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

DNEL long-term dermal (systemic), Workers: 283 mg/kg

DNEL long-term inhalative (systemic), Workers: 308 mg/m³

DNEL long-term dermal (systemic), Consumer: 121 mg/kg

DNEL long-term inhalative (systemic), Consumer: 37,2 mg/m³

DNEL long-term exposure oral (systemic effects), Consumer: 36 mg/kg

Hydrocarbons, C9, aromatics

Index No. 649-356-00-4 / EC No. 265-199-0 / CAS No. 64742-95-6

DNEL long-term dermal (systemic), Workers: 25 mg/kg

DNEL long-term inhalative (systemic), Workers: 150 mg/m³

DNEL long-term oral (repeated), Consumer: 11 mg/kg

DNEL long-term dermal (systemic), Consumer: 11 mg/kg

DNEL long-term inhalative (systemic), Consumer: 32 mg/m³

PNEC:

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

PNEC aquatic, freshwater: 0,635 mg/L

PNEC aquatic, marine water: 0,0635 mg/L

PNEC sediment, freshwater: 3,29 mg/kg

PNEC sediment, marine water: 0,329 mg/kg

PNEC, soil: 0,29 mg/kg

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

PNEC aquatic, freshwater: 19 mg/L

PNEC aquatic, marine water: 1,9 mg/L

PNEC aquatic, intermittent release: 190 mg/L

PNEC sediment, freshwater: 70,2 mg/kg

PNEC sediment, marine water: 7,02 mg/kg

PNEC, soil: 2,74 mg/kg

PNEC sewage treatment plant (STP): 4168 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 5 / 10

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	violet
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	140 °C Source: Hydrocarbons, C9, aromatics
Flammability:	Combustible liquid.
Lower and upper explosion limit:	
Lower explosion limit:	1,28 Vol-%
Upper explosion limit:	14 Vol-% Source: (2-methoxymethylethoxy)propanol
Flash point:	> 61 °C
Auto-ignition temperature:	207 °C Source: (2-methoxymethylethoxy)propanol
Decomposition temperature:	not applicable
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	< 135 mm²/s
Viscosity at 20 °C:	28 s 4 mm Method: DIN 53211
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	5 mbar Method: calculated. Source: 2-methoxy-1-methylethyl acetate
Density and/or relative density:	
Density at 20 °C:	0,95 g/cm³ Method: ISO 2811, part 3
Relative vapour density:	not applicable
particle characteristics:	not applicable

9.2. Other information

Solvent separation test: **< 3 weight-% (ADR/RID)**

Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 6 / 10

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

2-methoxy-1-methylethyl acetate

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 402

dermal, LD50, Rat: > 5000 mg/kg

inhalative (vapours), LC0, Rat: > 4345 ppm (6 h)

inhalative (dust and mist), LC50, Rat: > 23,8 mg/L (6 h)

(2-methoxymethylethoxy)propanol

oral, LD50, Rat: > 5000 mg/kg

dermal, LD50, Rabbit: > 5000 mg/kg

Hydrocarbons, C9, aromatics

oral, LD50, Rat: > 2000 mg/kg

dermal, LD50, Rabbit: > 2000 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

(2-methoxymethylethoxy)propanol

Skin

no irritation

eyes

Hydrocarbons, C9, aromatics

Skin

Repeated exposure may cause skin dryness or cracking.

Respiratory or skin sensitisation

(2-methoxymethylethoxy)propanol

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

(2-methoxymethylethoxy)propanol

Evaluation No data available

Hydrocarbons, C9, aromatics

Specific target organ toxicity (single exposure), Irritation Evaluation May cause respiratory irritation.

Specific target organ toxicity (single exposure), drowsiness Evaluation May cause drowsiness or dizziness.

Aspiration hazard

(2-methoxymethylethoxy)propanol

Aspiration hazard; Evaluation Represents no obvious danger of aspiration due to its physical properties

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 7 / 10

Hydrocarbons, C9, aromatics
Aspiration hazard

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
Aspiration hazard

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
There is no information available on the preparation itself .
Do not allow to enter into surface water or drains.

12.1. Toxicity

2-methoxy-1-methylethyl acetate

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 134 mg/L (96 h)
Method: OECD 203
Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 500 mg/L (48 h)
Method: Richtlinie 67/548/EWG, Anhang V, C.2.
Algae toxicity, EC50, Selenastrum capricornutum: > 1000 mg/L (72 h)
Method: OECD 201
Bacteria toxicity, EC10, Activated sludge: > 1000 mg/L (30 min)
Method: ISO 8192

(2-methoxymethylethoxy)propanol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 10000 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1919 mg/L (48 h)

Hydrocarbons, C9, aromatics

Daphnia toxicity, EC50 1 - 10 mg/L (48 h); Evaluation estimated
Fish toxicity, LC50 1 - 10 mg/L; Evaluation estimated
Algae toxicity, EC50 1 - 10 mg/L; Evaluation estimated
Bacteria toxicity, EC50: > 100 mg/L ; Evaluation estimated

Long-term Ecotoxicity

2-methoxy-1-methylethyl acetate

Fish toxicity, NOEC, Oryzias latipes (Ricefish): 47,5 mg/L (14 D)
Method: OECD 204
Daphnia toxicity, NOEC, Daphnia magna (Big water flea): > 100 mg/L 100 (21 D)
Method: OECD 202

Hydrocarbons, C9, aromatics

Fish toxicity, LC50 (96 h)
Daphnia toxicity, NOEC

12.2. Persistence and degradability

(2-methoxymethylethoxy)propanol

: 75 % (28 D); Evaluation Readily biodegradable (according to OECD criteria).
Method: OECD F
: 93 % (13 D)
Method: OECD 302B/ ISO 9888/ EEC 92/69/V, C.9

Hydrocarbons, C9, aromatics

:

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 8 / 10

12.3. Bioaccumulative potential

(2-methoxymethylethoxy)propanol
Partition coefficient: n-octanol/water: 1,01

12.4. Mobility in soil

(2-methoxymethylethoxy)propanol
: Evaluation No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable

Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code -

Sea transport (IMDG)

EmS-No. not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 9 / 10

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

This product is not classified according to Directive 2012/18/EU.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 138

VOC-value (in g/L) ASTM D2369: 138

National regulations

Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Other information:

Switzerland:

Volatile organic compounds (VOC) content in percent by weight: 15

Denmark:

PR-No.:

MAL code (MAL code in mixture):

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information

Full text of classification in section 3

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: KG404B1ADX10 Classic BaseOil COLOR
Print date: 05.04.2023 Revision date: 17.03.2023
Version: 15.0003 Issue date: 17.03.2023

EN
Page 10 / 10

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.