

						Parkett will das Beste!
Article Print o Versio		XS81DUO2BK10 05.04.2023 6.0002	AquaSeal GreenS Revision date: 21. Issue date: 21.03.	03.2023	EN Page 1 / 7	
SEC	TION 1: Id	entification of the	substance/mixtu	ure and of the com	pany/undertaking	
1.1.						
	Article No.	(manufacturer/supp e/designation	ier)	XS81DUO2BK10 AquaSeal GreenSta abZ-Nr. Z-157.10-4 Stat.Warennummer	7	
1.2.	Relevant i	dentified uses of th	e substance or mi	xture and uses advis	ed against	
	paint and/o	dentified uses or paint related mate for industrial and pro			-	
		sed against for injecting or spra	ying.			
1.3.	Details of	the supplier of the	safety data sheet			
	Berger-Sei	ke - Klebstoffe - Bauk raße 2		ser/distributor) Telephone: +49 635 Telefax: +49 6359 /		
	Departme Laboratory E-mail	nt responsible for i	nformation:	Sicherheitsdaten@	berger-seidle.de	
1.4.	24-hour en (BLG)	y telephone numbe nergency number: +4 nergency number in	9 700 24112112	888271 or +11 49 700	24112112 (BLG)	
SEC		azards identificati			· · ·	
2.1.		tion of the substan				
		tion according to R				
	The mixtur	e is classified as not	nazardous accordir	ng to regulation (EC) N	NO 1272/2008 [CLP].	
2.2.	Label elen	nonte				
2.2.		according to Regul	ation (FC) No. 1272	2/2008 [CL P]		
	Hazard pie					
	inazara pr	stog. and				
	Hazard sta	atements				
		not appl	cable			
	Precaution	nary statements				
		not appli				
		mponents for label not appli	cable			
	Suppleme EUH208	2-methy	3 1,2-benzisothiazol- -2H-isothiazol-3- on	e (3:1). May produce	nass of 5-chloro-2- methyl-2H an allergic reaction.	-isothiazol-3-one and
	EUH210	Safety d	ata sheet available o		-	
2.3.	Other haz	ards				
	No informa	ation available.				

Other information

Read label before use. If medical advice is needed, have product container or label at hand. Keep out of reach of children.

SECTION 3: Composition/information on ingredients

VOODELLOODILLO



rticle No.: rint date: ersion:	XS81DUO2BK10 05.04.2023 6.0002	AquaSeal GreenStar Matt/Satin Revision date: 21.03.2023 Issue date: 21.03.2023	EN Page 2 / 7	
Descrip		ased surface finishes, solvent content up	p to 5%, N-methylpyrrolidone-f	ree
		egulation (EC) No 1272/2008 [CLP]		
	REACH	Na		
EC No.	REACH	NO.		
EC NO. CAS NO				weight-%

not applicable

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing



Article No.:	XS81DUO2BK10	AquaSeal GreenStar Matt/Satin
Print date:	05.04.2023	Revision date: 21.03.2023
Version:	6.0002	Issue date: 21.03.2023

EN Page 3 / 7

agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection



Article No.: Print date: Version:	XS81DUO2BK10 05.04.2023 6.0002	AquaSeal GreenStar Matt/Satin Revision date: 21.03.2023 Issue date: 21.03.2023	EN Page 4 / 7	

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Physical state:	Liquid
	Colour:	refer to chapter 1.
	Odour:	characteristic
	Odour threshold:	not applicable
	Melting point/freezing point:	not applicable
	Initial boiling point and boiling range:	100 °C
		Source: Water
	Flammability:	not applicable
	Lower and upper explosion limit:	
	Lower explosion limit:	0,86 Vol-%
	Upper explosion limit:	11,6 Vol-% Source: 2-(2-ethoxyethoxy)ethanol
	Electronic to the	
	Flash point:	not applicable
	Auto-ignition temperature:	165 °C Source: Dipropylene glycol dimethyl ether, mixture of isomers
	Decomposition tomperature:	not applicable
	Decomposition temperature:	not applicable
	pH at 20 °C:	not applicable
	Cinematic viscosity (40°C):	< 135 mm²/s
	Viscosity at 20 °C:	24 s 4 mm
		Method: DIN 53211
	Solubility(ies):	
	Water solubility at 20 °C:	miscible
	Partition coefficient: n-octanol/water:	see section 12
	Vapour pressure at 20 °C:	23 mbar
		Method: calculated.
		Source: Water
	Density and/or relative density: Density at 20 °C:	1,05 g/cm³
		Method: ISO 2811, part 3
	Relative vapour density:	not applicable
	particle characteristics:	not applicable
9.2.	Other information	
	Solvent separation test:	< 3 weight-% (ADR/RID)
SEC	TION 10: Stability and reactivity	
OLC	non io. Stability and reactivity	

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions



Article No.:	XS81DUO2BK10	AquaSeal GreenStar Matt/Satin		
Print date:	05.04.2023	Revision date: 21.03.2023	EN	
Version:	6.0002	Issue date: 21.03.2023	Page 5 / 7	

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. **Persistence and degradability** Toxicological data are not available.

Toxicological data are not available.

12.3. **Bioaccumulative potential** Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil



				Parkett will aas Deste.
Article Print d /ersio	late:	XS81DUO2BK10 05.04.2023 6.0002	AquaSeal GreenStar Matt/Satin Revision date: 21.03.2023 Issue date: 21.03.2023	EN Page 6 / 7
	Toxicologi	cal data are not avail	able.	
12.5.	Results of	f PBT and vPvB ass	essment	
	The substa	ances in the mixture	to not meet the PBT/vPvB criteria according	ig to REACH, annex XIII.
12.6.		e disrupting propert ation available.	es	
12.7.		erse effects ation available.		
SEC	TION 13: [Disposal consider	ations	
13.1.	Waste trea	atment methods		
	Recomme Do not allo	ow to enter into surfa	ce water or drains. This material and its co	ontainer must be disposed of in a safe way. Waste
	-	-	2008/98/EC, covering waste and dangerous	
	List of pro 080112		waste designations in accordance with int and varnish other than those mentioned	
	Recomme		ge ay be recycled. Vessels not properly empti	ed are special waste.
SEC	TION 14: 1	Fransport informa	tion	·
		•	of this transport regulation.	
14.1.	-	er or ID number		
			not applicable	
14.2.	UN prope	r shipping name		
14.3	Transport	hazard class(es)		
			not applicable	
14.4.	Packing g	roup		
			not applicable	
14.5.		ental hazards		
		port (ADR/RID)	not applicable	
	Marine pol		not applicable	
14.6.		recautions for user		
	case of an	always in closed, upr accident or leakage n safe handling: see		ersons transporting the product know what to do in
	Further in	formation		
	Land tran	sport (ADR/RID)		
		triction code	-	
	Sea trans	port (IMDG)		
	EmS-No.	· · · /	not applicable	
14.7.		ransport in bulk ac	cording to IMO instruments	
		ort as bulk according	-	
SEC.	TION 15: F	Regulatory inform	ation	
10.1.	Safety, ne		ntal regulations/legislation specific for t	

EU legislation

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] This product is not classified according to Directive 2012/18/EU.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]



Article No.: Print date: Version:	XS81DUO2BK10 05.04.2023 6.0002	AquaSeal GreenStar Matt/Satin Revision date: 21.03.2023 Issue date: 21.03.2023	EN Page 7 / 7	

VOC-value (in g/L) ISO 11890-2: 63

VOC-value (in g/L) ASTM D2369: 175

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/j) ; VOC limit value: 140 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 57

National regulations

Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Other information:

Switzerland:

Volatile organic compounds (VOC) content in percent by weight: 0 Denmark: PR-No.: 4421516

MAL code (MAL code in mixture): 00-1(00-1)

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Appreviations and a	cronyins
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous
	Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative
E	

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version