# according to US OSHA Hazard Communication Standard (29 CFR 1



XZ15-0000-0AA AquaSeal UV Plus

Version 1.0 Revision date May 17, 2024 Print date May 17, 2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

### Trade name/designation

XZ15-0000-0AA AquaSeal UV Plus
UFI: 7K49-X0KM-K00G-Q8Y2

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

### Relevant identified uses

Reserved for industrial and professional use.

### Uses advised against

Do not use for injecting or spraying.

### 1.3 Details of the supplier of the safety data sheet

### Supplier

Berger-Seidle GmbH Maybachstr. 2 67269 Grünstadt Germany

### Department responsible for information

E-mail (competent person) Sicherheitsdaten@berger-seidle.de

### 1.4 Emergency telephone number

Emergency telephone number

+1 872 5888271

24 hr. emergency phone number

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Skin Sens. 1 H317 May cause an allergic skin reaction.

### 2.2 Label elements

## Labeling according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

# **Hazard pictograms**





GHS07 GHS08

### Signal word

Warning

### **Hazard statements**

H361 Suspected of damaging fertility or the unborn child.

H317 May cause an allergic skin reaction.

### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P201 Obtain special instructions before use.

P261 Avoid breathing vapours.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves and eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of water and soap.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

Page 1/9 US (en\_GB)

# according to US OSHA Hazard Communication Standard (29 CFR 1



XZ15-0000-0AA

AquaSeal UV Plus

Version 1.0 Revision date May 17, 2024

Print date May 17, 2024

P501

Dispose of contents/container to industrial incineration plant.

# Hazard components for labelling

Reaction mass of 104810-47-1 and 104810-48-2

Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate

### 2.3 Hazards not otherwise classified (HNOC)

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# **SECTION 3: Composition/information on ingredients.**

### 3.2 Mixtures

#### Description

Wassser, Lösemittel und Tenside

### **Hazardous ingredients**

CAS No. EC No. Index No.	Substance name REACH No.	weight-%
- 400-830-7 -	Reaction mass of 104810-47-1 and 104810-48-2 Skin Sens. 1 H317 / Aquatic Chronic 2 H411	5,00 < 7,00
1065336-91-5 915-687-0	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate Skin Sens. 1A H317 / Repr. 2 H361 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	3,00 < 5,00

#### Remark

Full text of H-phrases: see section 16.

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

### Following inhalation

In case of irregular breathing or respiratory arrest provide artificial respiration. Remove casualty to fresh air and keep warm and at rest.

# Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

# Self-protection of the first aider

First aider: Pay attention to self-protection!

# 4.2 Most important symptoms and effects, both acute and delayed

### Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Page 2/9 US (en\_GB)

# according to US OSHA Hazard Communication Standard (29 CFR 1



XZ15-0000-0AA

AquaSeal UV Plus

Version 1.0 Revision date May 17, 2024

Print date May 17, 2024

### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

### Unsuitable extinguishing media

Strong water jet

### 5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

### 5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

#### For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

#### For cleaning up

Clean using cleansing agents. Do not use solvents.

### 6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

### Advices on safe handling

Avoid contact with skin, eyes and clothes. Personal protection equipment: see section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

# Advices on general occupational hygiene

When using do not eat, drink or smoke.

# 7.2 Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class

LGK12 - non-combustible liquids that cannot be assigned to any of the above storage classes

### Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Store in a well-ventilated and dry room at temperatures between 5 °C and 25 °C.

### 7.3 Specific end use(s)

Observe technical data sheet.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

# Occupational exposure limit values

Page 3/9 US (en\_GB)

# Safety Data Sheet according to US OSHA Hazard Communication Standard (29 CFR 1



XZ15-0000-0AA Version 1.0 AquaSeal UV Plus

Revision date May 17, 2024

Print date May 17, 2024

No data available

# **Biological limit values**

No data available

### **DNEL** worker

CAS No.	Substance name	DNEL type	DNEL value
	Reaction mass of 104810-47-1 and 104810-48-2	DNEL long-term dermal (systemic)	0.25 mg/kg
-	Reaction mass of 104810-47-1 and 104810-48-2	DNEL acute dermal, short-term (systemic)	0.35 mg/kg
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	DNEL long-term dermal (systemic)	2 mg/kg
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	DNEL long-term inhalative (systemic)	3.53 mg/m³

# **DNEL Consumer**

CAS No.	Substance name	DNEL type	DNEL value
	Reaction mass of 104810-47-1 and 104810-48-2	DNEL long-term dermal (systemic)	0.025 mg/kg
	Reaction mass of 104810-47-1 and 104810-48-2	DNEL long-term inhalative (systemic)	0.085 mg/m <sup>3</sup>
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	DNEL long-term dermal (systemic)	1 mg/kg
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	DNEL long-term inhalative (systemic)	0.87 mg/m³

# **PNEC**

CAS No.	Substance name	PNEC type	PNEC Value
	Reaction mass of 104810-47-1 and 104810-48-2	PNEC soil, freshwater	mg/kg
	Reaction mass of 104810-47-1 and 104810-48-2	PNEC sediment, marine water	mg/kg
	Reaction mass of 104810-47-1 and 104810-48-2	PNEC sediment, freshwater	mg/kg
-	Reaction mass of 104810-47-1 and 104810-48-2	PNEC aquatic, marine water	ng/L
-	Reaction mass of 104810-47-1 and 104810-48-2	PNEC sewage treatment plant (STP)	mg/L
_	Reaction mass of 104810-47-1 and 104810-48-2	PNEC aquatic, freshwater	μg/L
-	Reaction mass of 104810-47-1 and 104810-48-2	PNEC aquatic, intermittent release	μg/L
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	PNEC soil, freshwater	0.21 mg/kg
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	PNEC sediment, marine water	0.11 mg/kg
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	PNEC sediment, freshwater	1.05 mg/kg
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	PNEC sewage treatment plant (STP)	1 mg/L
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	PNEC aquatic, marine water	0 mg/L
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	PNEC aquatic, freshwater	0.002 mg/L

# 8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

# Personal protection equipment

Respiratory protection

Page 4/9 US (en\_GB)

# according to US OSHA Hazard Communication Standard (29 CFR 1



XZ15-0000-0AA AquaSeal UV Plus

Version 1.0 Revision date May 17, 2024 Print date May 17, 2024

In case of inadequate ventilation wear respiratory protection.

### **Hand protection**

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material >= 0.4 mm

Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

### Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

### Eye/face protection

Eye glasses with side protection: EN 166

#### **Body protection**

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Antistatic clothing including shoes are recommended.

### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state Liquid
Colour white

Odour characteristic
pH at 20.0 °C (100%) 8.2 - 8.4
Melting point/freezing point not determined

Initial boiling point and boiling range 100 °C

Source: Water

Flash point not applicable flammability not applicable Lower explosion limit at 20°C not determined Upper explosion limit at 20°C not determined Vapour pressure at 20°C 23 mbar Relative vapour density not applicable

Density at 20 °C 1.0 kg/l

Water solubility at 20°C partially soluble
Partition coefficient: n-octanol/water see section 12

Ignition temperature in °C 352 °C

Source: Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and

methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate

Decomposition temperature not determined

Viscosity at 20 °C < 80 mm²/s

particle characteristics not applicable

9.2 Other information

Solid content 10.0 % Water content 90 %

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

Page 5/9 US (en\_GB)

# according to US OSHA Hazard Communication Standard (29 CFR 1



XZ15-0000-0AA

AguaSeal UV Plus

Version 1.0 Revision date May 17, 2024

Print date May 17, 2024

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

### 10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

### 10.5 Incompatible materials

No further relevant information available.

### 10.6 Hazardous decomposition products

Decomposition products in case of fire: see section 5.

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

May cause an allergic skin reaction.

# Overall assessment on CMR properties

Suspected of damaging fertility or the unborn child.

# STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

# Aspiration hazard

Based on available data, the classification criteria are not met.

# Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

### 11.2 Information on other hazards

# **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

Based on available data, the classification criteria are not met.

### Fish toxicity

### Reaction mass of 104810-47-1 and 104810-48-2

LC50: = 2.8 mg/L (96 h)

LC50: = 3.8 mg/L (96 h)

Page 6/9 US (en\_GB)

# according to US OSHA Hazard Communication Standard (29 CFR 1



XZ15-0000-0AA AquaSeal UV Plus

Version 1.0 Revision date May 17, 2024 Print date May 17, 2024

# Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate

LC50: = 0.9 mg/L (96 h)

### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

## Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way.

## Waste codes/waste designations according to EWC/AVV

080111\* - Waste paint and varnish containing organic solvents or other dangerous substances

\* Hazardous waste according to Directive 2008/98/EC (waste framework directive).

### Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

### **SECTION 14: Transport information**

### 14.1 UN number or ID number

UN 3082

### 14.2 UN proper shipping name

### Land transport (US DoT 49 CFR)

Environmentally hazardous substance, liquid, n.o.s. (Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate, Reaction mass of 104810-47-1 and 104810-48-2)

### Sea transport (IMDG)

Environmentally hazardous substance, liquid, n.o.s. (contain Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate, Reaction mass of 104810-47-1 and 104810-48-2)

### Air transport (ICAO-TI / IATA-DGR)

Environmentally hazardous substance, liquid, n.o.s. (contain Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate, Reaction mass of 104810-47-1 and 104810-48-2)

### 14.3 Transport hazard class(es)

Land transport (US DoT 49 CFR) 9
Sea transport (IMDG) 9
Air transport (ICAO-TI / IATA-DGR) 9

## 14.4 Packing group

Land transport (US DoT 49 CFR)

Sea transport (IMDG)

Air transport (ICAO-TI / IATA-DGR)

III

### 14.5 Environmental hazards

Land transport (US DoT 49 CFR) ENVIRONMENTALLY HAZARDOUS

Sea transport (IMDG) Marine pollutant / Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl)

sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate

# 14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case

Page 7/9 US (en\_GB)

# according to US OSHA Hazard Communication Standard (29 CFR 1



XZ15-0000-0AA AquaSeal UV Plus

Version 1.0 Revision date May 17, 2024 Print date May 17, 2024

of an accident or leakage.

Advices on safe handling: see parts 6 - 8

### 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

#### 14.8 Additional information

### Land transport (US DoT 49 CFR)

Tunnel restriction code: -Limited quantity (LQ): 5 ltr

Hazard identification number (Kemler No.): 90

# Sea transport (IMDG)

EmS-No.: F-A, S-F Limited quantity (LQ): 5 ltr

### Air transport (ICAO-TI / IATA-DGR)

not applicable

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### **National regulations**

Observe in addition any national regulations!

SARA Title III Section 311/312 Hazard Categories: Refer to section 2 of the safety data sheet.

# **SECTION 16: Other information**

### List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of

exposure if it is conclusively proven that no other routes of exposure cause the hazard).

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

# Key literature references and sources for data

Data arise from reference works and literature.

### Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

**DNEL: Derived No-Effect Level** 

EAKV: European Waste Catalogue Directive

EC: Effective Concentration EC: European Community EN: European Standard

EU/EEA: European Economic Area

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

.

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Page 8/9 US (en\_GB)

# Safety Data Sheet according to US OSHA Hazard Communication Standard (29 CFR 1



XZ15-0000-0AA Version 1.0 AquaSeal UV Plus

Revision date May 17, 2024

Print date May 17, 2024

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

**UN: United Nations** 

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

# Indication of changes

\* Data changed compared with the previous version.

Page 9/9 US (en\_GB)