

Article Print c Versic	date: 11.02.2		Classic BaseOil CC Revision date: 11.0 Issue date: 18.11.2	2.2023	56142 US Page 1 / 8
SEC	TION 1: Identificat	ion of the	substance/mixtu	re and of the compa	ny/undertaking
1.1.	Product identifier				
	Article No. (manufac Trade name/designa		er)	KG403D9ADX10 Classic BaseOil COLC Rot/Red abZ-Nr. Z-157.10-47	DR
1.2.	Relevant identified	uses of the	e substance or mix	ture and uses advised	against
	Relevant identified paint and/or paint re		al		
	Uses advised again Do not use for inject Product is not intend	ing or spray	•		
1.3.	Details of the supp	lier of the s	afety data sheet		
	supplier (manufact Berger-Seidle GmbH Parkettlacke - Klebsi Maybachstraße 2 67269 Grünstadt Germany	1		er/distributor) Telephone: +49 6359 / Telefax: +49 6359 / 80	
	Department respon	sible for in	formation:		
	Laboratory E-mail			Sicherheitsdaten@ber	rger-seidle.de
1.4.	Emergency telepho 24-hour emergency			88271 or +11 49 700 24	1112112 (BLG)
SEC	TION 2: Hazards ic	lentificatio	on		
2.1.	Classification of th	e substanc	e or mixture		
	GHS-US classificat Flam. Liq. 4 / H227		Flammable liquids		Combustible liquid.
2.2.	Label elements				
	GHS-US labeling				
	Hazard pictograms				
	Warning				
	Hazard statements H227		ible liquid.		
	Precautionary state				
	P210 P280 P370 + P378 P403 P501	Wear pro In case o Store in a	f fire: Use extinguish well-ventilated plac	ye/face protection. iing powder or sand to e	-
	Hazard component	s for labell	ing		

2.3. Other hazards

Spontaneous ignition possible through autoxidation of cloths soaked in the product. (The same applies to dust and other paint-soaked items). The product itself is not self ignitive.

Other information

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

 Description
 Oils/waxes, containing solvents, aromatics removed

 Hazardous ingredients



Article No.: Print date: Version:	KG403D9ADX10 11.02.2023 14.0001	Classic BaseOil COLOR Revision date: 11.02.2023 Issue date: 18.11.2022	56142 US Page 2 / 8	

GHS-US classification

CAS No.	Designation // Remark	weight-%
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	7,5 - 10
85-44-9	phthalic anhydride	0,1 - 0,25

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).



Article No.:	KG403D9ADX10	Classic BaseOil COLOR
Print date:	11.02.2023	Revision date: 11.02.2023
Version:	14.0001	Issue date: 18.11.2022

56142 US Page 3 / 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet.Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

phthalic anhydride Index No. 607-009-00-4 / EC No. 201-607-5 / CAS No. 85-44-9 IDLH, TWA: 60 mg/m3 OSHA, TWA: 12 mg/m3; 2 ppm NIOSH, TWA: 6 mg/m3; 1 ppm ACGIH, TWA: 0,002 mg/m3 ACGIH, STEL: 0,005 mg/m3 Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value STEL : short-term occupational exposure limit value C : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)



Article No.:	KG403D9ADX10	Classic BaseOil COLOR	
Print date:	11.02.2023	Revision date: 11.02.2023	56142 US
Version:	14.0001	lssue date: 18.11.2022	Page 4 / 8

Thickness of the glove material > 0.4 mm; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Physical state: Colour:	Liquid red
	Odour:	characteristic
	Odour threshold:	not applicable
	Initial boiling point and boiling range:	179 °C
	initial boining point and boining range.	Source: Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
	Lower and upper explosion limit:	
	Lower explosion limit:	1,1 Vol-%
	Upper explosion limit:	14 Vol-%
		Source: (2-methoxymethylethoxy)propanol
	Flash point:	> 61 °C
	Auto-ignition temperature:	207 °C
		Source: (2-methoxymethylethoxy)propanol
	Decomposition temperature:	not applicable
	pH at 20 °C:	not applicable
	Cinematic viscosity (40°C):	< 135 mm²/s
	Viscosity at 20 °C:	28 s 4 mm
		Method: DIN 53211
	Solubility(ies):	
	Water solubility at 20 °C:	insoluble
	Partition coefficient: n-octanol/water:	see section 12
	Vapour pressure at 20 °C:	0,7 mbar
		Method: calculated. Source: Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
	Density and/or relative density:	
	Density at 20 °C:	0,94 g/cm³
		Method: ISO 2811, part 3
	Relative vapour density:	not applicable
	particle characteristics:	not applicable
9.2.	Other information	
	Solvent separation test:	< 3 weight-% (ADR/RID)
SEC	TION 10: Stability and reactivity	

10.1. Reactivity



Article No.:	KG403D9ADX10	Classic BaseOil COLOR	
Print date:	11.02.2023	Revision date: 11.02.2023	56142 US
Version:	14.0001	Issue date: 18.11.2022	Page 5 / 8

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials** not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

phthalic anhydride oral, LD50, Rat: 1530 mg/kg dermal, LD50, Rabbit: 3160 mg/kg inhalative, Rat: 0,21 mg/L (1 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

phthalic anhydride Skin (4 h) eyes

Respiratory or skin sensitisation

phthalic anhydride Skin: Respiratory system:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

phthalic anhydride

Specific target organ toxicity (single exposure), Irritation

Aspiration hazard

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Aspiration hazard

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself . The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

11.2. Information on other hazards



Article No.:	KG403D9ADX10	Classic BaseOil COLOR
Print date:	11.02.2023	Revision date: 11.02.2023
Version:	14.0001	Issue date: 18.11.2022

56142 US Page 6 / 8

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

phthalic anhydride Partition coefficient: n-octanol/water: 1,6

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regula		regulation.	
	14.1.	UN number or ID number	
			not applicable
	14.2.	UN proper shipping name	
	14.3.	Transport hazard class(es)	
			not applicable
	14.4.	Packing group	
			not applicable
	14.5.	Environmental hazards	
		Land transport (ADR/RID)	not applicable
		Marine pollutant	not applicable
	116	Special pressutions for user	

14.6. Special precautions for user



Article No.:	KG403D9ADX10	Classic BaseOil COLOR
Print date:	11.02.2023	Revision date: 11.02.2023
Version:	14.0001	Issue date: 18.11.2022

56142 US Page 7 / 8

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG)

EmS-No.

not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

US Federal regulations

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] This product is not classified according to Directive 2012/18/EU.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 97 VOC-value (in g/L) ASTM D2369: 97

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/f) ; VOC limit value: 700 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 97

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

TSCA: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Derived No-Effect Level

SECTION 16: Other information

DIN

DNEL

Full text of classification in section 3:				
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.		
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.		
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.		
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.		
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.		
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.		
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.		
Classification proce	edure			
Classification for mix	tures and used evaluation method according to re	gulation (EC) No 1272/2008 [CLP]		
Flam. Liq. 4	Flammable liquids	On basis of test data.		
Abbreviations and a	acronyms			
ADR	European Agreement concerning the Internation	nal Carriage of Dangerous Goods by Road		
OEL	Occupational Exposure Limit Value			
BLV	Biological Limit Value			
CAS	Chemical Abstracts Service			
CLP	Classification, Labelling and Packaging			
CMR	Carcinogenic, Mutagenic and Reprotoxic			

German Institute for Standardization / German industrial standard



Print date:	KG403D9ADX10 11.02.2023 14.0001	Classic BaseOil COLOR Revision date: 11.02.2023 Issue date: 18.11.2022	56142 US Page 8 / 8	
EAKV	Europea	n Waste Catalogue Directive		
EC		Concentration		
EC	Europea	n Community		
EN		n Standard		
IATA-DGR	Internatio	onal Air Transport Association – D	angerous Goods Regulations	
IBC Code	Internation	onal Code for the Construction and	d Equipment of Ships carrying Dangerous Chemicals in	Bulk
ICAO-TI	Internatio	onal Civil Aviation Organization T	echnical Instructions for the Safe Transport of Dang	jerous
	Goods b	y Air		
IMDG Code International Maritim		onal Maritime Code for Dangerous	Goods	
•		onal Organization for Standardizat	ion	
LC	Lethal C	oncentration		
LD	Lethal D			
MARPOL	Maritime	Pollution: The International Conve	ention for the Prevention of Pollution from Ships	
OECD	Organisa	ation for Economic Cooperation an	d Development	
PBT		nt, bioaccumulative, toxic		
PNEC		d No Effect Concentration		
REACH	•	tion, Evaluation, Authorisation and		
RID	•		arriage of Dangerous Goods by Rail	
UN	United N			
VOC		Organic Compounds		
vPvB	very per	sistent and very bioaccumulative		
Eurthan info	rmation			

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version