

Article Print c Versic	late:	KG906Z8ADJ10 11.02.2023 10.0003	Classic OutdoorOil Revision date: 11.0 Issue date: 25.01.2)2.2023	56142 US Page 1 / 9
SEC	TION 1: Idei	ntification of the	e substance/mixtu	re and of the compa	any/undertaking
1.1.	Product ide Article No. (r Trade name,	manufacturer/supp	lier)	KG906Z8ADJ10 Classic OutdoorOil Gr Grün/Green Stat. Warennummer 3	
1.2.	Relevant ide	entified uses of th	ne substance or mix	ture and uses advised	d against
	paint and/or	entified uses paint related mate	rial		
		or injecting or spra ot intended for con			
1.3.	Details of th	e supplier of the	safety data sheet		
	Berger-Seidl Parkettlacke Maybachstra 67269 Grüns Germany	e GmbH - Klebstoffe - Bau ıße 2		er/distributor) Telephone: +49 6359 Telefax: +49 6359 / 80	
	Laboratory E-mail			Sicherheitsdaten@bei	rger-seidle.de
1.4.		telephone number in ergency number in		88271 or +11 49 700 24	4112112 (BLG)
SEC	TION 2: Haz	ards identificat	ion		
2.1.		on of the substan	ce or mixture		
2.2.	GHS-US cla Flam. Liq. 4 Label eleme	/ H227	Flammable liquids		Combustible liquid.
	GHS-US lab Hazard picte				
	Warni	ng			
	Hazard state H227		tible liquid.		
	Precautionary statements				
	P210 P280 P370 + P378 P403 P501	Wear pr In case Store in	otective gloves and e of fire: Use extinguish a well-ventilated plac	eye/face protection. hing powder or sand to e	-
		ponents for labe			

2.3. Other hazards

Spontaneous ignition possible through autoxidation of cloths soaked in the product. (The same applies to dust and other paint-soaked items). The product itself is not self ignitive.

Other information

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Oils/waxes, high in solvents, aromatics removed Hazardous ingredients



Article No.:	KG906Z8ADJ10	Classic OutdoorOil Grün	
Print date:	11.02.2023	Revision date: 11.02.2023	56142 US
Version:	10.0003	Issue date: 25.01.2023	Page 2 / 9

GHS-US classification

CAS No.	Designation // Remark	weight-%
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	25 - 50
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	7,5 - 10
64742-47-8	Distillates (petroleum), hydrotreated light	1 - 2,5
64742-95-6	Hydrocarbons, C9, aromatics	1 - 2,5
22464-99-9	2-ethylhexanoic acid, zirconium salt	0,25 - 0,5
85-44-9	phthalic anhydride	0,1 - 0,25

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media alcohol resistant foam, carbon dioxide, Powder, spray mist, (water) Unsuitable extinguishing media strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions



Article No.:	KG906Z8ADJ10	Classic OutdoorOil Grün	
Print date:	11.02.2023	Revision date: 11.02.2023	56142 US
Version:	10.0003	Issue date: 25.01.2023	Page 3 / 9

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

phthalic anhydride Index No. 607-009-00-4 / EC No. 201-607-5 / CAS No. 85-44-9 IDLH, TWA: 60 mg/m3 OSHA, TWA: 12 mg/m3; 2 ppm NIOSH, TWA: 6 mg/m3; 1 ppm ACGIH, TWA: 0,002 mg/m3 ACGIH, STEL: 0,005 mg/m3 Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value STEL : short-term occupational exposure limit value C : peak limitation

DNEL:

Hydrocarbons, C9, aromatics



Article No.:	KG906Z8ADJ10	Classic OutdoorOil Grün	
Print date:	11.02.2023	Revision date: 11.02.2023	56142 US
Version:	10.0003	Issue date: 25.01.2023	Page 4 / 9

Index No. 649-356-00-4 / EC No. 265-199-0 / CAS No. 64742-95-6 DNEL long-term dermal (systemic), Workers: 25 mg/kg DNEL long-term inhalative (systemic), Workers: 150 mg/m³ DNEL long-term oral (repeated), Consumer: 11 mg/kg DNEL long-term dermal (systemic), Consumer: 11 mg/kg DNEL long-term inhalative (systemic), Consumer: 32 mg/m³

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	green
Odour:	characteristic
Odour threshold:	not applicable
Initial boiling point and boiling range:	140 °C
	Source: Hydrocarbons, C9, aromatics
Lower and upper explosion limit:	
Lower explosion limit:	0,82 Vol-%
Upper explosion limit:	14 Vol-%
	Source: (2-methoxymethylethoxy)propanol
Flash point:	> 61 °C
Auto-ignition temperature:	201 °C
	Source: Distillates (petroleum), hydrotreated light
Decomposition temperature:	not applicable
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	< 80 mm²/s
Viscosity at 20 °C:	14 s 4 mm
	Method: DIN 53211
Solubility(ies):	



Print d Versio		KG906Z8ADJ10 11.02.2023 10.0003	Classic Outdoor Revision date: 1 Issue date: 25.0	1.02.2023	56142 US Page 5 / 9	
	Water so	ubility at 20 °C:		insoluble		
		coefficient: n-octan	ol/water:	see section 12		
	Vapour pr	essure at 20 °C:		0,9 mbar		
				Method: calculat Source: Hydroca	ed. ırbons, C9, aromatics	
	Density ar Density a	nd/or relative densi t 20 °C:	ty:	0,91 g/cm³ Method: ISO 281	1, part 3	
	Relative v	apour density:		not applicable		
		naracteristics:		not applicable		
9.2.	Other info	rmation				
	Solvent se	eparation test:		< 3 weight-% (Al	DR/RID)	
SEC	TION 10: \$	Stability and react	tivity			
10.1.	Reactivity	ation available.				
10.2.	Chemical	stability	mmended regulati	ions for storage an	nd handling. Further information on correct storage: refer to	
10.3.		y of hazardous reac y from strong acids, s		strong oxidizing ag	gents to avoid exothermic reactions.	
10.4.	Conditions to avoid Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.					
10.5.	Incompatible materials not applicable					
10.6.	 Hazardous decomposition products Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxid smoke, nitrogen oxides. 			high temperatures, e.g.: carbon dioxide, carbon monoxide		
SEC	TION 11: 1	Foxicological info	rmation			
11.1.	Informatio	on on hazard classe	es as defined in F	Regulation (EC) N	o 1272/2008	
	Acute tox	icity				
	dermal, L	hydride 0, Rat: 1530 mg/kg .D50, Rabbit: 3160 n e, Rat: 0,21 mg/L (`				
	oral, LD5 dermal, L oral, LC5	ons, C10-C13, n-alk 0, Rat: > 5000 mg/kg .D50, Rabbit: > 5000 0, Rat: > 5 mg/L OECD 403	g	cyclics, < 2% aron	natics	
	Hydrocarbons, C9, aromatics oral, LD50, Rat: > 2000 mg/kg dermal, LD50, Rabbit: > 2000 mg/kg					
	Skin corrosion/irritation; Serious eye damage/eye irritation					
	-	phthalic anhydride Skin (4 h)				
	-	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	Hydrocarbons, C9, aromatics Skin					



Article No.:	KG906Z8ADJ10	Classic OutdoorOil Grün
Print date: Version:	11.02.2023 10.0003	Revision date: 11.02.2023 Issue date: 25.01.2023
VCI3I011.	10.0005	1350C Uale. 20.01.2020

56142 US Page 6 / 9

Respiratory or skin sensitisation

phthalic anhydride Skin:

Respiratory system:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

2-ethylhexanoic acid, zirconium salt

Reproductive toxicity

STOT-single exposure; STOT-repeated exposure

phthalic anhydride

Specific target organ toxicity (single exposure), Irritation

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Specific target organ toxicity (single exposure) Evaluation The substance or mixture is not rated as target-organ-toxic Hydrocarbons. C9. aromatics

Hydrocarbons, C9, aromatics

Specific target organ toxicity (single exposure), Irritation Evaluation May cause respiratory irritation.

Specific target organ toxicity (single exposure), drowsiness Evaluation May cause drowsiness or dizziness.

Aspiration hazard

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Aspiration hazard; Evaluation May be fatal if swallowed and enters airways.

Hydrocarbons, C9, aromatics Aspiration hazard

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Aspiration hazard

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself . The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

11.2. Information on other hazards

Endocrine disrupting properties No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Fish toxicity, LL0, Oncorhynchus mykiss (Rainbow trout) (96 h) Daphnia toxicity, EL0, Daphnia magna (Big water flea): 1000 mg/L (48 h) Algae toxicity, EL0, Pseudokirchneriella subcapitata: 72 mg/L (72 h)

Hydrocarbons, C9, aromatics

Daphnia toxicity, EC50 1 - 10 mg/L (48 h); Evaluation estimated Fish toxicity, LC50 1 - 10 mg/L; Evaluation estimated Algae toxicity, EC50 1 - 10 mg/L; Evaluation estimated Bacteria toxicity, EC50: > 100 mg/L ; Evaluation estimated



56142 US Page 7 / 9

Article No.:	KG906Z8ADJ10	Classic OutdoorOil Grün
Print date:	11.02.2023	Revision date: 11.02.2023
Version:	10.0003	Issue date: 25.01.2023

Long-term Ecotoxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Fish toxicity, NOELR, Oncorhynchus mykiss (Rainbow trout): 0,1 mg/L (28 D) Daphnia toxicity, NOELR, Daphnia magna (Big water flea): 0,18 mg/L (21 D)

Hydrocarbons, C9, aromatics Fish toxicity, LC50 (96 h) Daphnia toxicity, NOEC

12.2. Persistence and degradability

Hydrocarbons, C9, aromatics

12.3. Bioaccumulative potential

phthalic anhydride

Partition coefficient: n-octanol/water: 1,6

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package

Recommendation Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

		not applicable
14.2.	UN proper shipping name	
14.3.	Transport hazard class(es)	
	• • • • •	not applicable
14.4.	Packing group	
		not applicable
14.5.	Environmental hazards	
	Land transport (ADR/RID)	not applicable
	Marine pollutant	not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.



Article No.:	KG906Z8ADJ10	Classic OutdoorOil Grün
Print date:	11.02.2023	Revision date: 11.02.2023
Version:	10.0003	Issue date: 25.01.2023

56142 US Page 8 / 9

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG)

EmS-No.

not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

US Federal regulations

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] This product is not classified according to Directive 2012/18/EU.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 467 VOC-value (in g/L) ASTM D2369: 467

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/i) ; VOC limit value: 500 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 467

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

TSCA: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging the unborn child.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Classification procedure		

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP] Flam. Liq. 4 Flammable liquids On basis of test data.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road			
OEL	Occupational Exposure Limit Value			
BLV	Biological Limit Value			
CAS	Chemical Abstracts Service			
CLP	Classification, Labelling and Packaging			
CMR	Carcinogenic, Mutagenic and Reprotoxic			
DIN	German Institute for Standardization / German industrial standard			



Article No.: Print date: Version:	KG906Z8ADJ10 11.02.2023 10.0003	Classic OutdoorOil Grün Revision date: 11.02.2023 Issue date: 25.01.2023	56142 US Page 9 / 9			
DNEL	Derived	Derived No-Effect Level				
EAKV	Europea	European Waste Catalogue Directive				
EC	Effective	Effective Concentration				
EC	Europea	European Community				
EN	Europea	European Standard				
IATA-DGR	Internati	International Air Transport Association – Dangerous Goods Regulations				
IBC Code		International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk				
ICAO-TI	Internati	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous				
	Goods b	oy Air				
IMDG Code		International Maritime Code for Dangerous Goods				
ISO	Internati	International Organization for Standardization				
LC	Lethal C	Lethal Concentration				
LD	Lethal D					
MARPOL	Maritime	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships				
OECD	Organisation for Economic Cooperation and Development					
PBT	persistent, bioaccumulative, toxic					
PNEC	Predicted No Effect Concentration					
REACH		Registration, Evaluation, Authorisation and Restriction of Chemicals				
RID	•	Regulations concerning the International Carriage of Dangerous Goods by Rail				
UN	0	United Nations				
VOC		Volatile Organic Compounds				
vPvB	very per	sistent and very bioaccumulative				
Eurthor inf	ormation					

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.