

Article Print c Versic	late:	KG908L2ADJ10 11.02.2023 15.0003	Classic OutdoorOil Revision date: 11.0 Issue date: 25.01.2	2.2023	56142 US Page 1 / 8
SEC	TION 1: Ider	tification of the	substance/mixtu	re and of the com	ipany/undertaking
1.1.	Product iden Article No. (n Trade name/	nanufacturer/suppl	lier)	KG908L2ADJ10 Classic OutdoorOil Teak/Teak Stat. Warennumme	
1.2.	Relevant ide	ntified uses of th	e substance or mix	ture and uses advis	sed against
	-	paint related mater	rial		
		d against or injecting or spra t intended for cons			
1.3.	Details of th	e supplier of the	safety data sheet		
	Berger-Seidle Parkettlacke Maybachstra 67269 Grüns Germany	e GmbH - Klebstoffe - Bauo ße 2		er/distributor) Telephone: +49 63 Telefax: +49 6359 /	
	Laboratory E-mail			Sicherheitsdaten@	berger-seidle.de
1.4.		telephone number in a	e r side USA: +1 872 58	88271 or +11 49 700) 24112112 (BLG)
SEC	TION 2: Haz	ards identificati	ion		
2.1.	Classificatio	on of the substant ssification	ce or mixture		
2.2.	Flam. Liq. 4 / Label eleme GHS-US labe Hazard picto Warni	nts eling ograms ng	Flammable liquids		Combustible liquid.
	Hazard state H227		tible liquid.		
		ry statements	, , , , , ,	<i>c</i> .	n 1.11 · ···· · · · · · · · · · · · · · ·
	P210Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.P280Wear protective gloves and eye/face protection.P370 + P378In case of fire: Use extinguishing powder or sand to extinguish.P403Store in a well-ventilated place.P501Dispose of contents/container to industrial incineration plant.				
	Hazard components for labelling				

2.3. Other hazards

Spontaneous ignition possible through autoxidation of cloths soaked in the product. (The same applies to dust and other paint-soaked items). The product itself is not self ignitive.

Other information

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Oils/waxes, high in solvents, aromatics removed Hazardous ingredients



Article No.:	KG908L2ADJ10	Classic OutdoorOil Teak	56142 US
Print date:	11.02.2023	Revision date: 11.02.2023	
Version:	15.0003	Issue date: 25.01.2023	Page 2 / 8

GHS-US classification

CAS No.	Designation // Remark	weight-%
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	25 - 50
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	7,5 - 10
64742-47-8	Distillates (petroleum), hydrotreated light	1 - 2,5
22464-99-9	2-ethylhexanoic acid, zirconium salt	0,25 - 0,5
85-44-9	phthalic anhydride	0,1 - 0,25

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.



Article No .:	KG908L2ADJ10	Classic OutdoorOil Teak	
Print date:	11.02.2023	Revision date: 11.02.2023	56142 US
Version:	15.0003	Issue date: 25.01.2023	Page 3 / 8

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

phthalic anhydride Index No. 607-009-00-4 / EC No. 201-607-5 / CAS No. 85-44-9 IDLH, TWA: 60 mg/m3

OSHA, TWA: 12 mg/m3; 2 ppm

NIOSH, TWA: 6 mg/m3; 1 ppm

ACGIH, TWA: 0,002 mg/m3 ACGIH, STEL: 0,005 mg/m3 Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value STEL : short-term occupational exposure limit value C : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment



Article No.:	KG908L2ADJ10	Classic OutdoorOil Teak	
Print date:	11.02.2023	Revision date: 11.02.2023	56142 US
Version:	15.0003	Issue date: 25.01.2023	Page 4 / 8

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	brown
Odour:	characteristic
Odour threshold:	not applicable
Initial boiling point and boiling range:	179 °C Source: Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
Lower and upper explosion limit: Lower explosion limit: Upper explosion limit:	0,92 Vol-% 14 Vol-% Source: (2-methoxymethylethoxy)propanol
Flash point:	> 61 °C
Auto-ignition temperature:	201 °C Source: Distillates (petroleum), hydrotreated light
Decomposition temperature:	not applicable
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	< 80 mm²/s
Viscosity at 20 °C:	14 s 4 mm Method: DIN 53211
Solubility(ies): Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	0,7 mbar Method: calculated. Source: Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
Density and/or relative density: Density at 20 °C:	0,90 g/cm³ Method: ISO 2811, part 3
Relative vapour density:	not applicable



Article Print c	date: 11.02.2023	Revision date: 11.02.2023	56142 US	
/ersic	on: 15.0003	Issue date: 25.01.2023	Page 5 / 8	
	particle characteristics:	not applicable		
9.2.	Other information			
	Solvent separation test:	< 3 weight-% (ADR/	RID)	
SEC	TION 10: Stability and re-	activity		
10.1.	Reactivity No information available.			
10.2.	Chemical stability Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.			
		eactions ls, strong bases and strong oxidizing agent	ts to avoid exothermic reactions.	
10.4.	Conditions to avoid Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.			
10.5.	Incompatible materials not applicable			
10.6.	Hazardous decomposition products Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.			
SEC	TION 11: Toxicological ir	nformation		
11.1.	Information on hazard class	sses as defined in Regulation (EC) No 1	272/2008	
	Acute toxicity			
	phthalic anhydride oral, LD50, Rat: 1530 mg/l dermal, LD50, Rabbit: 316 inhalative, Rat: 0,21 mg/L	0 mg/kg		
	Hydrocarbons, C10-C13, n- oral, LD50, Rat: > 5000 mg dermal, LD50, Rabbit: > 50 oral, LC50, Rat: > 5 mg/L Method: OECD 403		cs	
	Skin corrosion/irritation; S	Serious eye damage/eye irritation		
	phthalic anhydride Skin (4 h) eyes			
	Hydrocarbons, C10-C13, n- eyes	alkanes, isoalkanes, cyclics, < 2% aromati	cs	
	Respiratory or skin sensit	isation		
	phthalic anhydride Skin: Respiratory system:			
		alkanes, isoalkanes, cyclics, < 2% aromati	cs	
	-	city, mutagenicity and toxicity for reprod		
	2-ethylhexanoic acid, zircon Reproductive toxicity			
	STOT-single exposure; ST	OT-repeated exposure		
	phthalic anhydride			

phthalic anhydride

Specific target organ toxicity (single exposure), Irritation

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Specific target organ toxicity (single exposure) Evaluation The substance or mixture is not rated as target-organ-toxic

Aspiration hazard



Article No.:	KG908L2ADJ10	Classic OutdoorOil Teak	
Print date:	11.02.2023	Revision date: 11.02.2023	56142 US
Version:	15.0003	lssue date: 25.01.2023	Page 6 / 8

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Aspiration hazard; Evaluation May be fatal if swallowed and enters airways.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Aspiration hazard

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatique, amvosthenia, drowsiness, in serious cases; unconsciousness, Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eve irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers.See chapters 2 and 15 for details.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Fish toxicity, LL0, Oncorhynchus mykiss (Rainbow trout) (96 h) Daphnia toxicity, EL0, Daphnia magna (Big water flea): 1000 mg/L (48 h) Algae toxicity, EL0, Pseudokirchneriella subcapitata: 72 mg/L (72 h)

Long-term Ecotoxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Fish toxicity, NOELR, Oncorhynchus mykiss (Rainbow trout): 0,1 mg/L (28 D) Daphnia toxicity, NOELR, Daphnia magna (Big water flea): 0,18 mg/L (21 D)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

phthalic anhydride Partition coefficient: n-octanol/water: 1,6

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation



			Parkett Will	aus Desre.
Article No.: Print date: Version:	KG908L2ADJ10 11.02.2023 15.0003	Classic OutdoorOil Teak Revision date: 11.02.2023 Issue date: 25.01.2023	56142 US Page 7 / 8	
	Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.			
		s/waste designations in accordance aint and varnish other than those me		
Rec	oropriate disposal / Packa commendation -contaminated packages m	ge ay be recycled. Vessels not properly	emptied are special waste.	
SECTION	14: Transport informa	tion		
No	dangerous good in sense	of this transport regulation.		
14.1. UN	number or ID number			
		not applicable		
14.2. UN	proper shipping name			
14.3. Tra r	nsport hazard class(es)			
		not applicable		
14.4. Pac	king group			
		not applicable		
14.5. Env	rironmental hazards			
	d transport (ADR/RID)	not applicable		
Mari	ine pollutant	not applicable		
14.6. Spe	cial precautions for user			
case	nsport always in closed, up e of an accident or leakage ices on safe handling: see		that persons transporting the product know wha	to do in
Furt	ther information			
Lan	d transport (ADR/RID)			
Tuni	nel restriction code	-		
Sea	transport (IMDG)			
	S-No.	not applicable		
14.7. Mar	itime transport in bulk ac	cording to IMO instruments		
No t	transport as bulk according	IBC - Code.		
SECTION	15: Regulatory inform	ation		
15.1. Safe	ety, health and environme	ntal regulations/legislation specifi	c for the substance or mixture	
	US Federal regulations			
	-	ontrol of major-accident hazards i	nvolving dangerous substances [Seveso-III-I) irective1
		cording to Directive 2012/18/EU.		

This product is not classified according to Directive 2012/18/EU.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 470 VOC-value (in g/L) ASTM D2369: 470

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/i) ; VOC limit value: 500 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 470

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

TSCA: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption



Article No.:	KG908L2ADJ10	Classic OutdoorOil Teak	
Print date:	11.02.2023	Revision date: 11.02.2023	56142 US
Version:	15.0003	Issue date: 25.01.2023	Page 8 / 8

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification in section 3:				
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.		
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.		
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging the unborn child.		
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.		
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.		
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.		
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.		
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or		
		breathing difficulties if inhaled.		
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.		
Classification proce	edure			
Classification for mix	tures and used evaluation method according to re	gulation (EC) No 1272/2008 [CLP]		
Flam. Liq. 4	Flammable liquids	On basis of test data.		
Abbreviations and a	acronyms			
ADR	European Agreement concerning the Internation	al Carriage of Dangerous Goods by Road		
OEL	Occupational Exposure Limit Value	, , , , , , , , , , , , , , , , , , ,		
BLV	Biological Limit Value			
CAS	Chemical Abstracts Service			
CLP	Classification, Labelling and Packaging			
CMR	Carcinogenic, Mutagenic and Reprotoxic			
DIN	German Institute for Standardization / German in	ndustrial standard		
DNEL	Derived No-Effect Level			
EAKV	European Waste Catalogue Directive			
EC	Effective Concentration			
EC	European Community			
EN	European Standard			
IATA-DGR	International Air Transport Association – Danger			
IBC Code		ipment of Ships carrying Dangerous Chemicals in Bulk		
ICAO-TI		ical Instructions for the Safe Transport of Dangerous		
	Goods by Air			
IMDG Code	International Maritime Code for Dangerous Good	ds		
ISO	International Organization for Standardization			
LC	Lethal Concentration			
	Lethal Dose	for the Dressention of Dollation from Ohing		
MARPOL	Maritime Pollution: The International Convention			
OECD	Organisation for Economic Cooperation and Development			
PBT	persistent, bioaccumulative, toxic			
PNEC	Predicted No Effect Concentration			
REACH RID	Registration, Evaluation, Authorisation and Rest Regulations concerning the International Carriag			
UN	United Nations	Je u Dangerous Goous by Rall		
VOC	-			
VOC Volatile Organic Compounds vPvB very persistent and very bioaccumulative				
Further information	Further information			

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.