

| Article Print d Versio | ate: | KG908L3ADJ10 11.02.2023 15.0003 | Classic OutdoorOil Revision date: 11.0 Issue date: 25.01.2 | 2.2023 | 56142 US Page 1 / 8 | |
|--|--|---|--|---|------------------------|--|
| SEC | TION 1: Iden | tification of the | substance/mixtu | re and of the com | npany/undertaking | |
| 1.1. | Product ider Article No. (n Trade name/ | nanufacturer/supp | lier) | KG908L3ADJ10 Classic OutdoorOil Palisander/Rosewo Stat. Warennumme | bod | |
| 1.2. | Relevant ide | ntified uses of th | e substance or mix | ture and uses advis | sed against | |
| Relevant identified uses paint and/or paint related material Uses advised against Do not use for injecting or spraying. | | | | | | |
| | | t intended for con | | | | |
| 1.3. | Details of th | e supplier of the | safety data sheet | | | |
| | Berger-Seidle Parkettlacke Maybachstra 67269 Grüns Germany | e GmbH - Klebstoffe - Bau ße 2 | | er/distributor) Telephone: +49 63 Telefax: +49 6359 / | | |
| | Laboratory E-mail | | | Sicherheitsdaten@ | eberger-seidle.de | |
| 1.4. | | telephone number in rgency number in | e r side USA: +1 872 58 | 88271 or +11 49 700 | 0 24112112 (BLG) | |
| SEC | TION 2: Haza | ards identificati | on | | | |
| 2.1. Classificat | | on of the substan | ce or mixture | | | |
| 0.0 | GHS-US class Flam. Liq. 4 / | H227 | Flammable liquids | | Combustible liquid. | |
| 2.2. | Label eleme GHS-US labo | eling | | | | |
| | Hazard picto | - | | | | |
| | Warnin Hazard state | • | | | | |
| | H227 | | tible liquid. | | | |
| | Precautionary statements | | | | | |
| | P210Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.P280Wear protective gloves and eye/face protection.P370 + P378In case of fire: Use extinguishing powder or sand to extinguish.P403Store in a well-ventilated place.P501Dispose of contents/container to industrial incineration plant. | | | to extinguish. | | |
| | Hazard components for labelling | | | | | |

2.3. Other hazards

Spontaneous ignition possible through autoxidation of cloths soaked in the product. (The same applies to dust and other paint-soaked items). The product itself is not self ignitive.

Other information

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Oils/waxes, high in solvents, aromatics removed Hazardous ingredients



GHS-US classification

| CAS No. | Designation // Remark | weight-% |
|------------|---|------------|
| | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 25 - 50 |
| | Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics | 7,5 - 10 |
| 64742-47-8 | Distillates (petroleum), hydrotreated light | 1 - 2,5 |
| 22464-99-9 | 2-ethylhexanoic acid, zirconium salt | 0,25 - 0,5 |
| 85-44-9 | phthalic anhydride | 0,1 - 0,25 |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.



| Article No.: | KG908L3ADJ10 | Classic OutdoorOil Palisander | |
|--------------|--------------|-------------------------------|------------|
| Print date: | 11.02.2023 | Revision date: 11.02.2023 | 56142 US |
| Version: | 15.0003 | lssue date: 25.01.2023 | Page 3 / 8 |

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

phthalic anhydride Index No. 607-009-00-4 / EC No. 201-607-5 / CAS No. 85-44-9 IDLH, TWA: 60 mg/m3

OSHA, TWA: 12 mg/m3; 2 ppm

NIOSH, TWA: 6 mg/m3; 1 ppm

ACGIH, TWA: 0,002 mg/m3 ACGIH, STEL: 0,005 mg/m3 Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value STEL : short-term occupational exposure limit value C : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment



| Article No.: | KG908L3ADJ10 | Classic OutdoorOil Palisander | |
|--------------|--------------|-------------------------------|------------|
| Print date: | 11.02.2023 | Revision date: 11.02.2023 | 56142 US |
| Version: | 15.0003 | lssue date: 25.01.2023 | Page 4 / 8 |

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state: | Liquid |
|--|---|
| Colour: | brown |
| Odour: | characteristic |
| Odour threshold: | not applicable |
| Initial boiling point and boiling range: | 179 °C Source: Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics |
| Lower and upper explosion limit: Lower explosion limit: Upper explosion limit: | 0,94 Vol-% 14 Vol-% Source: (2-methoxymethylethoxy)propanol |
| Flash point: | > 61 °C |
| Auto-ignition temperature: | 201 °C Source: Distillates (petroleum), hydrotreated light |
| Decomposition temperature: | not applicable |
| pH at 20 °C: | not applicable |
| Cinematic viscosity (40°C): | < 80 mm²/s |
| Viscosity at 20 °C: | 14 s 4 mm Method: DIN 53211 |
| Solubility(ies): Water solubility at 20 °C: | insoluble |
| Partition coefficient: n-octanol/water: | see section 12 |
| Vapour pressure at 20 °C: | 0,7 mbar Method: calculated. Source: Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics |
| Density and/or relative density: Density at 20 °C: | 0,91 g/cm³ Method: ISO 2811, part 3 |
| Relative vapour density: | not applicable |



| Article Print c Versic | late: | KG908L3ADJ10 11.02.2023 15.0003 | Classic OutdoorOil Palisander Revision date: 11.02.2023 Issue date: 25.01.2023 | 56142 US Page 5 / 8 |
|------------------------------|--|--|--|--|
| | particle ch | aracteristics: | not applicable | |
| 9.2. | Other info | rmation | | |
| | Solvent se | paration test: | < 3 weight-% (ADR/F | RID) |
| SEC | TION 10: S | tability and react | livity | |
| 10.1. | Reactivity No informa | tion available. | | |
| 10.2. | Chemical s Stable whe section 7. | • | mmended regulations for storage and ha | andling. Further information on correct storage: refer to |
| 10.3. | | of hazardous read from strong acids, s | c tions strong bases and strong oxidizing agents | s to avoid exothermic reactions. |
| 10.4. | | n applying the reco | mmended regulations for storage and ha sition byproducts may form with exposu | andling. Further information on correct storage: refer t re to high temperatures. |
| 10.5. | Incompatil not applica | ble materials ble | | |
| 10.6. | Hazardous | decomposition production decomposition byp decomposition byp ogen oxides. | | temperatures, e.g.: carbon dioxide, carbon monoxide |
| SEC | TION 11: T | oxicological info | rmation | |
| 11.1. | Informatio | n on hazard classe | es as defined in Regulation (EC) No 12 | 272/2008 |
| Acute toxicity | | | | |
| | dermal, L | hydride), Rat: 1530 mg/kg D50, Rabbit: 3160 n , Rat: 0,21 mg/L (` | | |
| | oral, LD50 dermal, Ll oral, LC50 | ons, C10-C13, n-alk), Rat: > 5000 mg/kg D50, Rabbit: > 5000), Rat: > 5 mg/L OECD 403 | | cs |
| | Skin corro | sion/irritation; Ser | ious eye damage/eye irritation | |
| | phthalic an Skin (4 h) eyes | | | |
| | | ons, C10-C13, n-alk | anes, isoalkanes, cyclics, < 2% aromatic | CS |
| | - | y or skin sensitisa | tion | |
| | phthalic an Skin: Respirato | hydride ry system: | | |
| | - | | anes, isoalkanes, cyclics, < 2% aromatic | CS |
| | - | | , mutagenicity and toxicity for reprodu | |
| | - | anoic acid, zirconiun tive toxicity | n salt | |
| | • | • | -repeated exposure | |
| | phthalic an | hydride | | |

phthalic anhydride

Specific target organ toxicity (single exposure), Irritation

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Specific target organ toxicity (single exposure) Evaluation The substance or mixture is not rated as target-organ-toxic

Aspiration hazard



| Article No.: | KG908L3ADJ10 | Classic OutdoorOil Palisander | 56440 110 |
|--------------|--------------|-------------------------------|------------|
| Print date: | 11.02.2023 | Revision date: 11.02.2023 | 56142 US |
| Version: | 15.0003 | Issue date: 25.01.2023 | Page 6 / 8 |

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Aspiration hazard; Evaluation May be fatal if swallowed and enters airways.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Aspiration hazard

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself . The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Fish toxicity, LL0, Oncorhynchus mykiss (Rainbow trout) (96 h) Daphnia toxicity, EL0, Daphnia magna (Big water flea): 1000 mg/L (48 h) Algae toxicity, EL0, Pseudokirchneriella subcapitata: 72 mg/L (72 h)

Long-term Ecotoxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Fish toxicity, NOELR, Oncorhynchus mykiss (Rainbow trout): 0,1 mg/L (28 D) Daphnia toxicity, NOELR, Daphnia magna (Big water flea): 0,18 mg/L (21 D)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

phthalic anhydride Partition coefficient: n-octanol/water: 1,6

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation



| Article Print d Versio | ate: | KG908L3ADJ10 11.02.2023 15.0003 | Classic OutdoorOil Palisander Revision date: 11.02.2023 Issue date: 25.01.2023 | 56142 US Page 7 / 8 | | |
|------------------------------|---|--|--|---|--|--|
| | Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe disposal according to directive 2008/98/EC, covering waste and dangerous waste. | | | | | |
| | • | • | | | | |
| | List of proposed waste codes/waste designations in accordance with EWC 080112 waste paint and varnish other than those mentioned in 08 01 11 | | | | | |
| | Recommer | | ge ay be recycled. Vessels not properly e | emptied are special waste. | | |
| SEC | TION 14: TI | ransport informa | tion | | | |
| | No danger | ous good in sense | of this transport regulation. | | | |
| 14.1. | UN number | r or ID number | | | | |
| | | | not applicable | | | |
| 14.2. | UN proper | shipping name | | | | |
| 14 3 | Transport I | nazard class(es) | | | | |
| 11.0. | inditoport | | not applicable | | | |
| 14.4. | Packing gr | oup | | | | |
| | | | not applicable | | | |
| 14.5. | Environme | ntal hazards | | | | |
| | Land transp | ort (ADR/RID) | not applicable | | | |
| | Marine pollu | utant | not applicable | | | |
| 14.6. | Special pre | ecautions for user | | | | |
| | case of an a | lways in closed, upr accident or leakage. safe handling: see | - | nat persons transporting the product know what to do in | | |
| | Further info | ormation | | | | |
| | Land trans | port (ADR/RID) | | | | |
| | Tunnel restr | iction code | - | | | |
| | Sea transp | ort (IMDG) | | | | |
| | EmS-No. | . , | not applicable | | | |
| 14.7. | Maritime tr | ansport in bulk ac | cording to IMO instruments | | | |
| | No transpor | t as bulk according | IBC - Code. | | | |
| SEC | TION 15: R | egulatory inform | ation | | | |
| 15.1. | Safety, hea | Ith and environme | ntal regulations/legislation specific | for the substance or mixture | | |
| | - | regulations | | | | |
| | Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] | | | | | |

This product is not classified according to Directive 2012/18/EU.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 465

VOC-value (in g/L) ASTM D2369: 465

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/i) ; VOC limit value: 500 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 465

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

TSCA: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption



| Article No.: | KG908L3ADJ10 | Classic OutdoorOil Palisander | |
|--------------|--------------|-------------------------------|------------|
| Print date: | 11.02.2023 | Revision date: 11.02.2023 | 56142 US |
| Version: | 15.0003 | lssue date: 25.01.2023 | Page 8 / 8 |

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

| Full text of classification in section 3: | | | | | |
|--|--|--|--|--|--|
| Asp. Tox. 1 / H304 | Aspiration hazard | May be fatal if swallowed and enters airways. | | | |
| Flam. Liq. 3 / H226 | Flammable liquids | Flammable liquid and vapour. | | | |
| Repr. 2 / H361 | Reproductive toxicity | Suspected of damaging the unborn child. | | | |
| Acute Tox. 4 / H302 | Acute toxicity (oral) | Harmful if swallowed. | | | |
| STOT SE 3 / H335 | STOT-single exposure | May cause respiratory irritation. | | | |
| Skin Irrit. 2 / H315 | Skin corrosion/irritation | Causes skin irritation. | | | |
| Eye Dam. 1 / H318 | Serious eye damage/eye irritation | Causes serious eye damage. | | | |
| Resp. Sens. 1 / H334 | Respiratory or skin sensitisation | May cause allergy or asthma symptoms or | | | |
| | | breathing difficulties if inhaled. | | | |
| Skin Sens. 1 / H317 | Respiratory or skin sensitisation | May cause an allergic skin reaction. | | | |
| Classification proce | edure | | | | |
| Classification for mix | tures and used evaluation method according to re- | gulation (EC) No 1272/2008 [CLP] | | | |
| Flam. Liq. 4 | Flammable liquids | On basis of test data. | | | |
| Abbreviations and a | acronyms | | | | |
| ADR | European Agreement concerning the Internation | al Carriage of Dangerous Goods by Road | | | |
| OEL | Occupational Exposure Limit Value | 6 6 , | | | |
| BLV | Biological Limit Value | | | | |
| CAS | Chemical Abstracts Service | | | | |
| CLP | Classification, Labelling and Packaging | | | | |
| CMR | Carcinogenic, Mutagenic and Reprotoxic | | | | |
| DIN | German Institute for Standardization / German in | ndustrial standard | | | |
| DNEL | Derived No-Effect Level | | | | |
| EAKV | European Waste Catalogue Directive | | | | |
| EC | Effective Concentration | | | | |
| EC | European Community | | | | |
| EN | European Standard | | | | |
| IATA-DGR | International Air Transport Association – Danger | | | | |
| IBC Code | | ipment of Ships carrying Dangerous Chemicals in Bulk | | | |
| ICAO-TI | | ational Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous | | | |
| | | Goods by Air | | | |
| IMDG Code | | ternational Maritime Code for Dangerous Goods | | | |
| ISO | International Organization for Standardization | | | | |
| LC | Lethal Concentration | | | | |
| LD | Lethal Dose | | | | |
| MARPOL Maritime Pollution: The International Conve | | | | | |
| OECD | Organisation for Economic Cooperation and Development | | | | |
| PBT | persistent, bioaccumulative, toxic | | | | |
| PNEC | Predicted No Effect Concentration | | | | |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals | | | | |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail | | | | |
| UN VOC | United Nations | | | | |
| VOC Volatile Organic Compounds vPvB very persistent and very bioaccumulative | | | | | |
| | | | | | |
| Further information | | | | | |

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.