

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.: KP702044GZ10 SolvSeal SportMarking COLOR
Print date: 25.02.2023 Revision date: 25.02.2023 56142 US
Version: 22.0001 Issue date: 25.01.2023 Page 1 / 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier) KP702044GZ10
Trade name/designation SolvSeal SportMarking COLOR
Orange

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

paint and/or paint related material

Uses advised against

Do not use for injecting or spraying.
Product is not intended for consumer use.

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Berger-Seidle GmbH
Parkettlacke - Klebstoffe - Bauchemie Telephone: +49 6359 / 8005-0
Maybachstraße 2 Telefax: +49 6359 / 8005-170
67269 Grünstadt
Germany

Department responsible for information:

Laboratory
E-mail Sicherheitsdaten@berger-seidle.de

1.4. Emergency telephone number

24-hour emergency number in side USA: +1 872 5888271 or +11 49 700 24112112 (BLG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Carc. 1B / H350	Carcinogenicity	May cause cancer.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

2.2. Label elements

GHS-US labeling

Hazard pictograms



Danger

Hazard statements

H226 Flammable liquid and vapour.
H350 May cause cancer.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing vapours.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves and eye/face protection.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313 IF exposed or concerned: Get medical advice/attention.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.: KP702044GZ10 SolvSeal SportMarking COLOR
Print date: 25.02.2023 Revision date: 25.02.2023 56142 US
Version: 22.0001 Issue date: 25.01.2023 Page 2 / 12

P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Keep locked up.
P501 Dispose of contents/container to industrial incineration plant.

Hazard components for labelling

2.3. Other hazards

Spontaneous ignition possible through autoxidation of cloths soaked in the product. (The same applies to dust and other paint-soaked items). The product itself is not self ignitive.

Other information

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Oil epoxy resin sealants, high in solvents, aromatics removed

Hazardous ingredients

GHS-US classification

CAS No.	Designation // Remark	weight-%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	15 - 20
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	7,5 - 10
64742-95-6	Hydrocarbons, C9, aromatics	5 - 7,5
108-65-6	2-methoxy-1-methylethyl acetate	2,5 - 5
123-86-4	n-butyl acetate	1 - 2,5
22464-99-9	2-ethylhexanoic acid, zirconium salt	0,5 - 1
96-29-7	butanone oxime	0,1 - 0,25
85711-46-2	Fatty acids, C14-18 and C16-18-unsatd., maleated	0,1 - 0,25
2457-01-4	Barium bis(2-ethylhexanoate)	0,1 - 0,25

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.:	KP702044GZ10	SolvSeal SportMarking COLOR	
Print date:	25.02.2023	Revision date: 25.02.2023	56142 US
Version:	22.0001	Issue date: 25.01.2023	Page 3 / 12

medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.:	KP702044GZ10	SolvSeal SportMarking COLOR	
Print date:	25.02.2023	Revision date: 25.02.2023	56142 US
Version:	22.0001	Issue date: 25.01.2023	Page 4 / 12

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Naphtha (petroleum), hydrotreated heavy

Index No. 649-327-00-6 / EC No. 265-150-3 / CAS No. 64742-48-9

OSHA, PEL, STEL: 400 mg/m³; 100 ppm

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

ACGIH, TWA: 50 ppm

ACGIH, STEL: 150 ppm

IDLH, TWA: 1700 ppm

NIOSH, TWA: 710 mg/m³; 150 ppm

NIOSH, STEL: 950 mg/m³; 200 ppm

OSHA, TWA: 710 mg/m³; 150 ppm

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

C : peak limitation

DNEL:

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL acute dermal, short-term (systemic), Workers: 11 mg/kg

DNEL long-term dermal (systemic), Workers: 7 mg/kg

DNEL acute inhalative (local), Workers: 600 mg/m³

DNEL long-term inhalative (local), Workers: 300 mg/m³

DNEL long-term inhalative (systemic), Workers: 48

DNEL acute dermal, short-term (systemic), Consumer: 6 mg/kg

DNEL long-term dermal (systemic), Consumer: 6 mg/kg

DNEL acute inhalative (local), Consumer: 300 mg/m³

DNEL long-term inhalative (local), Consumer: 35,7 mg/m³

DNEL long-term inhalative (systemic), Consumer: 12

DNEL long-term exposure oral (systemic effects), Consumer: 2 mg/kg

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

DNEL long-term dermal (systemic), Workers: 153,5 mg/kg

DNEL long-term inhalative (systemic), Workers: 275 mg/m³

DNEL long-term oral (repeated), Consumer: 1,67 mg/kg

DNEL long-term dermal (systemic), Consumer: 54,8 mg/kg

DNEL long-term inhalative (systemic), Consumer: 33 mg/m³

Hydrocarbons, C9, aromatics

Index No. 649-356-00-4 / EC No. 265-199-0 / CAS No. 64742-95-6

DNEL long-term dermal (systemic), Workers: 25 mg/kg

DNEL long-term inhalative (systemic), Workers: 150 mg/m³

DNEL long-term oral (repeated), Consumer: 11 mg/kg

DNEL long-term dermal (systemic), Consumer: 11 mg/kg

DNEL long-term inhalative (systemic), Consumer: 32 mg/m³

PNEC:

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.: KP702044GZ10 SolvSeal SportMarking COLOR
Print date: 25.02.2023 Revision date: 25.02.2023
Version: 22.0001 Issue date: 25.01.2023

56142 US
Page 5 / 12

n-butyl acetate
Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4
PNEC aquatic, freshwater: 0,18 mg/L
PNEC aquatic, marine water: 0,018 mg/L
PNEC aquatic, intermittent release: 0,36 mg/L
PNEC sediment, freshwater: 0,981 mg/L
PNEC sediment, marine water: 0,0981 mg/L
PNEC, soil: 0,0903 mg/kg
PNEC sewage treatment plant (STP): 35,6 mg/L

2-methoxy-1-methylethyl acetate
Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6
PNEC aquatic, freshwater: 0,635 mg/L
PNEC aquatic, marine water: 0,0635 mg/L
PNEC sediment, freshwater: 3,29 mg/kg
PNEC sediment, marine water: 0,329 mg/kg
PNEC, soil: 0,29 mg/kg

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)
Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	orange
Odour:	characteristic
Odour threshold:	not applicable
Initial boiling point and boiling range:	110 °C Source: Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
Lower and upper explosion limit:	
Lower explosion limit:	1,38 Vol-%
Upper explosion limit:	10,8 Vol-% Source: 2-methoxy-1-methylethyl acetate
Flash point:	24 °C
Auto-ignition temperature:	200 °C

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.: KP702044GZ10 SolvSeal SportMarking COLOR
Print date: 25.02.2023 Revision date: 25.02.2023 56142 US
Version: 22.0001 Issue date: 25.01.2023 Page 6 / 12

Decomposition temperature:	Source: Naphtha (petroleum), hydrotreated heavy not applicable
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	< 700 mm²/s
Viscosity at 20 °C:	95 s 4 mm Method: DIN 53211
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	15 mbar Method: calculated. Source: n-butyl acetate
Density and/or relative density:	
Density at 20 °C:	1,03 g/cm³ Method: ISO 2811, part 3
Relative vapour density:	not applicable
particle characteristics:	not applicable
9.2. Other information	
Solvent separation test:	< 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

n-butyl acetate

oral, LD50, Rat: 10760 mg/kg

dermal, LD50, Rabbit: > 14100 mg/kg

2-methoxy-1-methylethyl acetate

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 402

dermal, LD50, Rat: > 5000 mg/kg

inhalative (vapours), LC0, Rat: > 4345 ppm (6 h)

inhalative (dust and mist), LC50, Rat: > 23,8 mg/L (6 h)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.: KP702044GZ10 SolvSeal SportMarking COLOR
Print date: 25.02.2023 Revision date: 25.02.2023
Version: 22.0001 Issue date: 25.01.2023

56142 US
Page 7 / 12

dermal, LD50, Rabbit: > 5000 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: > 4951 mg/L (4 h)
Method: OECD 403

Hydrocarbons, C9, aromatics
oral, LD50, Rat: > 2000 mg/kg
dermal, LD50, Rabbit: > 2000 mg/kg

Naphtha (petroleum), hydrotreated heavy
oral, LD50, Rat: > 5000 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: > 2000 mg/kg

Barium bis(2-ethylhexanoate)
oral, LD50, Rat
inhalative (vapours), LC50, Rat (4 h)

Fatty acids, C14-18 and C16-18-unsatd., maleated
oral, LD50, Rat: > 2000 mg/kg
Method: OECD 423

Skin corrosion/irritation; Serious eye damage/eye irritation

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
eyes

Hydrocarbons, C9, aromatics
Skin
Repeated exposure may cause skin dryness or cracking.

Respiratory or skin sensitisation

n-butyl acetate
Skin:
Respiratory system:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
: ; Evaluation No sensitising effect known

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

May cause cancer.

butanone oxime
Carcinogenicity

2-ethylhexanoic acid, zirconium salt
Reproductive toxicity

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

n-butyl acetate
Specific target organ toxicity (single exposure), drowsiness

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
Specific target organ toxicity (single exposure), drowsiness

Hydrocarbons, C9, aromatics
Specific target organ toxicity (single exposure), Irritation Evaluation May cause respiratory irritation.
Specific target organ toxicity (single exposure), drowsiness Evaluation May cause drowsiness or dizziness.

Naphtha (petroleum), hydrotreated heavy
Specific target organ toxicity (single exposure)

Aspiration hazard

n-butyl acetate
Aspiration hazard

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
Aspiration hazard

Hydrocarbons, C9, aromatics
Aspiration hazard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.: KP702044GZ10 SolvSeal SportMarking COLOR
Print date: 25.02.2023 Revision date: 25.02.2023 56142 US
Version: 22.0001 Issue date: 25.01.2023 Page 8 / 12

Naphtha (petroleum), hydrotreated heavy
Aspiration hazard

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

EC No. CAS No.	Designation	Classification according to Regulation (EC) No 1272/2008 [CLP]
202-496-6 96-29-7	butanone oxime	Carc. 1B

Remark

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
Do not allow to enter into surface water or drains.

12.1. Toxicity

n-butyl acetate

- Fish toxicity, LC50, *Leuciscus idus* (golden orfe): 62 mg/L (96 h)
- Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 72,8 mg/L (24 h)
- Algae toxicity, *Scenedesmus subspicatus*: 674,7 mg/L (72 h)
- Fish toxicity, *Lepomis macrochirus* (Bluegill): 100 mg/L (96 h)
- Fish toxicity, LC50, *Pimephales promelas* (fathead minnow): 18 mg/L (96 h)

2-methoxy-1-methylethyl acetate

- Fish toxicity, LC50, *Oncorhynchus mykiss* (Rainbow trout): 134 mg/L (96 h)
- Method: OECD 203
- Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): > 500 mg/L (48 h)
- Method: Richtlinie 67/548/EWG, Anhang V, C.2.
- Algae toxicity, EC50, *Selenastrum capricornutum*: > 1000 mg/L (72 h)
- Method: OECD 201
- Bacteria toxicity, EC10, Activated sludge: > 1000 mg/L (30 min)
- Method: ISO 8192

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

- Daphnia toxicity, EL50, *Daphnia magna* (Big water flea) 22 - 46 mg/L (48 h)
- Algae toxicity, EL50, *Pseudokirchneriella subcapitata*: > 1000 mg/L (72 h)
- Algae toxicity, NOELR, *Pseudokirchneriella subcapitata*: < 1 mg/L (72 h)
- Fish toxicity, LL50, *Oncorhynchus mykiss* (Rainbow trout) 10 - 30 mg/L (96 h)

Hydrocarbons, C9, aromatics

- Daphnia toxicity, EC50 1 - 10 mg/L (48 h); Evaluation estimated
- Fish toxicity, LC50 1 - 10 mg/L; Evaluation estimated
- Algae toxicity, EC50 1 - 10 mg/L; Evaluation estimated
- Bacteria toxicity, EC50: > 100 mg/L ; Evaluation estimated

Naphtha (petroleum), hydrotreated heavy

- Fish toxicity, LC50 (96 h)
- Algae toxicity, EL50: > 1000 mg/L (72 h)
- Method: OECD 201
- Daphnia toxicity, EL50: > 1000 mg/L (48 h)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.: KP702044GZ10 SolvSeal SportMarking COLOR
Print date: 25.02.2023 Revision date: 25.02.2023 56142 US
Version: 22.0001 Issue date: 25.01.2023 Page 9 / 12

Method: OECD 202
Fish toxicity, CL50: > 100 mg/L (96 h)
Method: OECD 202

Fatty acids, C14-18 and C16-18-unsatd., maleated
Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/L (48 h); Evaluation semistatic
Method: OECD 202
Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 100 mg/L (72 h); Evaluation semistatic
Method: OECD 201
Fish toxicity, LC50, Leuciscus idus (golden orfe): > 150 mg/L (48 h)
Method: DIN 38412
Bacteria toxicity, EC50, Activated sludge: > 1000 mg/L (3 h); Evaluation static test
Method: OECD 209

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

2-methoxy-1-methylethyl acetate
Fish toxicity, NOEC, Oryzias latipes (Ricefish): 47,5 mg/L (14 D)
Method: OECD 204
Daphnia toxicity, NOEC, Daphnia magna (Big water flea): > 100 mg/L 100 (21 D)
Method: OECD 202

Hydrocarbons, C9, aromatics
Fish toxicity, LC50 (96 h)
Daphnia toxicity, NOEC

12.2. Persistence and degradability

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
: 89 % (28 D)
Hydrocarbons, C9, aromatics
:

12.3. Bioaccumulative potential

n-butyl acetate
Partition coefficient: n-octanol/water: 1,81
Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.: KP702044GZ10 SolvSeal SportMarking COLOR
Print date: 25.02.2023 Revision date: 25.02.2023 56142 US
Version: 22.0001 Issue date: 25.01.2023 Page 10 / 12

SECTION 14: Transport information

- 14.1. **UN number or ID number**
UN 1263
- 14.2. **UN proper shipping name**
Land transport (ADR/RID): Paint
Sea transport (IMDG): PAINT
Air transport (ICAO-TI / IATA-DGR): Paint
- 14.3. **Transport hazard class(es)**
Land transport (ADR/RID): KEINE GÜTER DER KLASSE 3
bunch > 450 l class 3
Sea transport (IMDG) 3
for packages < = 450 litres Transport in accordance with 2.3.2.5 of the IMDG Code.
Air transport (ICAO-TI / IATA-DGR) 3
- 14.4. **Packing group**
III
- 14.5. **Environmental hazards**
Land transport (ADR/RID) not applicable
Marine pollutant not applicable
- 14.6. **Special precautions for user**
Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8
- Further information**
- Land transport (ADR/RID)**
Tunnel restriction code D/E
- Sea transport (IMDG)**
EmS-No. F-E, S-E
- 14.7. **Maritime transport in bulk according to IMO instruments**
No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

- 15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- US Federal regulations**
- Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]**
Category: P5c FLAMMABLE LIQUIDS
Quantity 1: 5000 t / Quantity 2: 50000 t
- Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**
VOC-value (in g/L) ISO 11890-2: 435
VOC-value (in g/L) ASTM D2369: 435
- Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**
VOC product category: (Cat. A/i) ; VOC limit value: 500 g/l
Maximum VOC content of the product in a ready to use condition (in g/L): 435
- National regulations**
- Restrictions of occupation**
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
- Substance/product listed in the following inventories:**
TSCA: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption
- 15.2. **Chemical Safety Assessment**
Chemical safety assessments for substances in this mixture were not carried out.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.: KP702044GZ10 SolvSeal SportMarking COLOR
Print date: 25.02.2023 Revision date: 25.02.2023
Version: 22.0001 Issue date: 25.01.2023

56142 US
Page 11 / 12

SECTION 16: Other information

Full text of classification in section 3:

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Skin Irrit. 3 / H316	Skin corrosion/irritation	Causes mild skin irritation.
Aquatic Acute 3 / H402	Hazardous to the aquatic environment	Harmful to aquatic organisms.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging the unborn child.
Carc. 1B / H350	Carcinogenicity	May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 3 / H301	Acute toxicity (oral)	Toxic if swallowed.
STOT SE 1 / H370	STOT-single exposure	Causes damage to organs (or state all organs affected, if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
Carc. 1B	Carcinogenicity	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
Aquatic Chronic 3	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations



Article No.:	KP702044GZ10	SolvSeal SportMarking COLOR	
Print date:	25.02.2023	Revision date: 25.02.2023	56142 US
Version:	22.0001	Issue date: 25.01.2023	Page 12 / 12

PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.