

Article Print c Versic	late:	KW04000AHJ10 03.03.2023 10.0000	Classic Plus Reakti Revision date: 27.0 Issue date: 05.11.2	2.2023	56142 US Page 1 / 9
SEC	TION 1: Ide	entification of the	substance/mixtu	re and of the	company/undertaking
1.1.	Product id	entifier			
		(manufacturer/suppl e/designation	ier)		10 eaktivvergütung nmer 32081090
1.2.	Relevant ic	lentified uses of th	e substance or mix	ture and uses a	advised against
	Uses advised against Do not use for injecting or spraying. Product is not intended for consumer use.				
1.3.	Details of t	he supplier of the	safety data sheet		
			ter/downstream us	er/distributor)	
	Berger-Seid Parkettlack Maybachstr 67269 Grür Germany	e - Klebstoffe - Baud aße 2	chemie	Telephone: +4 Telefax: +49 6	9 6359 / 8005-0 359 / 8005-170
	-	t responsible for i	nformation:		
	Laboratory E-mail			Sicherheitsdat	en@berger-seidle.de
1.4.		/ telephone numbe	r	Clonomonodul	
				88271 or +11 49	9 700 24112112 (BLG)
SEC	CTION 2: Hazards identification				
2.1.	Classification of the substance or mixture				
	GHS-US classificationHarmful if inhaled.Acute Tox. 4 / H332Acute toxicity (inhalative)Harmful if inhaled.Skin Sens. 1 / H317Respiratory or skin sensitisationMay cause an allergic skin reaction.STOT SE 3 / H335STOT-single exposureMay cause respiratory irritation.				
2.2.	Label elem	ents			
	GHS-US la				
	Hazard pic	tograms			
	Warning				
	Hazard sta				
	H332 H317		if inhaled. se an allergic skin re	action.	
	H335		se respiratory irritatio		
		ary statements	a othing vanaura		
	P261 P271		eathing vapours. voutdoors or in a wel	I-ventilated area	
	P272	Contami	nated work clothing	should not be all	owed out of the workplace.
	P280 P302 + P35		otective gloves and e KIN: Wash with plent		
	P304 + P34 P312				keep comfortable for breathing.
	P333 + P31		DISON CENTER or c itation or rash occurs		
	P362 + P36 P403 + P23		contaminated clothin		
	P405	Keep loo			
	P501	-	of contents/containe	r to industrial inc	ineration plant.
	mazard Col	nponents for label	iing		
2.3.	Other haza	ırds			



Print date: 03.0	'04000AHJ10Classic Plus I03.2023Revision date0000Issue date: 03	e: 27.02.2023	56142 US Page 2 / 9
------------------	---	---------------	------------------------

No information available.

Other information

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Preparations containing isocyanates Hazardous ingredients GHS-US classification

CAS No.	Designation // Remark	weight-%
	Hexamethylene diisocyanate, oligomers (isocyanurate type)	50 - 100
822-06-0	hexamethylene-di-isocyanate	0 25 - 0 5

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media alcohol resistant foam, carbon dioxide, Powder, spray mist, (water) Unsuitable extinguishing media strong water iet

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures



Article No.:	KW04000AHJ10		
Print date:	03.03.2023	Revision date: 27.02.2023	56142 US
Version:	10.0000	Issue date: 05.11.2022	Page 3 / 9

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

hexamethylene-di-isocyanate

Index No. 615-011-00-1 / EC No. 212-485-8 / CAS No. 822-06-0

ACGIH, TWA: 0,034 mg/m3; 0,005 ppm

NIOSH, TWA: 0,035 mg/m3; 0,005 ppm

NIOSH, C: 0,14 mg/m3; 0,02 ppm

ACGIH-BEI, TWA: 15 µg/g creatinine

Remark: 1,6-Hexamethylene diamine, Following hydrolysis:; urine; end of exposure or end of shift

Additional information

TWA : Long-term occupational exposure limit value STEL : short-term occupational exposure limit value C : peak limitation

DNEL:



Article No.:	KW04000AHJ10	Classic Plus Reaktivvergütung	
Print date:	03.03.2023	Revision date: 27.02.2023	56142 US
Version:	10.0000	lssue date: 05.11.2022	Page 4 / 9

hexamethylene-di-isocyanate

Index No. 615-011-00-1 / EC No. 212-485-8 / CAS No. 822-06-0 DNEL acute inhalative (local), Workers: 0,07 mg/m³

DNEL acute inhalative (systemic), Workers: 0,07 mg/m³

DNEL long-term inhalative (local), Workers: 0,035 mg/m³

DNEL long-term inhalative (systemic), Workers: 0,035 mg/m³

PNEC:

hexamethylene-di-isocyanate

Index No. 615-011-00-1 / EC No. 212-485-8 / CAS No. 822-06-0 PNEC aquatic, freshwater: > 77,4 µg/L Scenedesmus subspicatus PNEC aquatic, marine water: > 7,74 µg/L Scenedesmus subspicatus PNEC aquatic, intermittent release: 774 µg/L PNEC sediment, freshwater: > 0,0133 mg/kg PNEC, soil: > 0,0026 mg/kg

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid yellow
Odour:	characteristic
Odour threshold:	not applicable
Initial boiling point and boiling range:	not applicable
Lower and upper explosion limit: Lower explosion limit: Upper explosion limit:	not applicable not applicable
Flash point:	> 100 °C
Auto-ignition temperature:	not applicable
Decomposition temperature:	not applicable



						Parkett will das Beste!
Article Print c Versic	date:	KW04000AHJ10 03.03.2023 10.0000	Classic Plus Re Revision date: 2 Issue date: 05.2	27.02.2023	56142 US Page 5 / 9	
	pH at 20 °	C:		not applicable		
	Cinematic viscosity (40°C):		< 700 mm²/s			
	Viscosity	at 20 °C:		100 s 4 mm Method: DIN 532	11	
	Solubility Water so	(ies): Iubility at 20 °C:		insoluble		
		coefficient: n-octane	ol/water:	see section 12		
	Vapour p	ressure at 20 °C:		not applicable		
	Density a Density a	nd/or relative densit it 20 °C:	ty:	1,15 g/cm³ Method: ISO 281	1, part 3	
	Relative v	apour density:		not applicable		
	•	haracteristics:		not applicable		
9.2.	Other info					*
		eparation test:		< 3 weight-% (AD	R/RID)	
SEC	TION 10:	Stability and react	ivity			
10.1.	Reactivity	<i>I</i> ation available.				
10.2.	Chemical Stable wh section 7.		mmended regulat	tions for storage and	d handling. Further information or	ו correct storage: refer to
10.3.		Possibility of hazardous reactions Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.				
10.4.	Stable wh	Conditions to avoid Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.				
10.5.	Incompat	ible materials able				
10.6.	Hazardou	s decomposition pr s decomposition bypr trogen oxides.		n with exposure to h	igh temperatures, e.g.: carbon di	ioxide, carbon monoxide,
SEC	TION 11:	Toxicological info	rmation			
11.1.	Informatio	on on hazard classe	es as defined in	Regulation (EC) No	o 1272/2008	
	Acute tox	icity				
	Harmful if	inhaled.				
	oral, LDS Method: dermal, l	ylene-di-isocyanate 50, Rat: 746 mg/kg OECD 401 _D50, Rat: > 7000 mg e (dust and mist), LC				
	oral, LDs dermal, l	ylene diisocyanate, c 50, Rat: > 2500 mg/kg _D50, Rat: > 2000 mg e (dust and mist), LC	g g/kg			
	Skin corr	osion/irritation; Seri	ious eye damage	e/eye irritation		
	hexameth Skin eyes	ylene-di-isocyanate				

Respiratory or skin sensitisation

May cause an allergic skin reaction.



Article No.:	KW04000AHJ10	Classic Plus Reaktivvergütung
Print date:	03.03.2023	Revision date: 27.02.2023
Version:	10.0000	Issue date: 05.11.2022

56142 US Page 6 / 9

hexamethylene-di-isocyanate

Skin:

Respiratory system:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

hexamethylene-di-isocyanate

Specific target organ toxicity (single exposure), Irritation

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

hexamethylene-di-isocyanate Daphnia toxicity, EC0, Daphnia magna (Big water flea): > 89 mg/L (48 h) Method: European Union Bacteria toxicity, EC50: 842 mg/L (3 h) Algae, Desmodesmus subspicatus: > 77,4 (72 h) Fish toxicity, LC0:, Danio rerio (zebrafish): > 82,7 mg/L Algae, NOEC, Desmodesmus subspicatus: 11,7 mg/L (72 h)

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

hexamethylene-di-isocyanate Biodegradation, 67/548/EWG, Anhang V, C.4.D.: 42 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



	U		Parkett will das Beste!
Article No.: Print date: Version:	KW04000AHJ10 03.03.2023 10.0000	Classic Plus Reaktivvergütung Revision date: 27.02.2023 Issue date: 05.11.2022	56142 US Page 7 / 9
	rine disrupting proper rmation available.	ties	
12.7. Other a	adverse effects rmation available.		
SECTION 1	3: Disposal conside	ations	
	treatment methods		
Recom	oriate disposal / Produ mendation allow to enter into surfa		its container must be disposed of in a safe way. Waste
disposa	al according to directive	2008/98/EC, covering waste and dang	gerous waste.
080111	* Waste p	s/waste designations in accordance paint and varnish containing organic sc Directive 2008/98/EC (waste framewo	olvents or other dangerous substances
Recom	oriate disposal / Packa mendation ntaminated packages n	ge nay be recycled. Vessels not properly e	emptied are special waste.
SECTION 1	4: Transport informa	tion	
No dar	igerous good in sense	of this transport regulation.	
14.1. UN nui	nber or ID number		
14.2. UN pro	per shipping name	not applicable	
14.3. Transp	oort hazard class(es)	not applicable	
14.4. Packin	g group	not applicable	*
14.5. Enviro	nmental hazards		
Land tr	ansport (ADR/RID)	not applicable	
Marine	pollutant	not applicable	
14.6. Specia	I precautions for user		
case of	ort always in closed, up [:] an accident or leakage s on safe handling: see		hat persons transporting the product know what to do in
Furthe	r information		
	ransport (ADR/RID) restriction code	-	
Sea tra	insport (IMDG)		
EmS-N	0.	not applicable	
14.7. Maritin	ne transport in bulk ac	cording to IMO instruments	
No trar	sport as bulk according	IBC - Code.	
SECTION 1	5: Regulatory inform	ation	
15.1. Safety.	health and environme	ental regulations/legislation specific	for the substance or mixture
-	leral regulations		
		control of major-accident hazards in ccording to Directive 2012/18/EU.	volving dangerous substances [Seveso-III-Directive]
	ve 2010/75/EU on indu alue (in g/L) ISO 11890-	strial emissions [Industrial Emissio 2: 5	ns Directive]

VOC-value (in g/L) ISO 11890-2: 5 VOC-value (in g/L) ASTM D2369: 5 National regulations



Article No.:	KW04000AHJ10	- 3 3	
Print date:	03.03.2023	Revision date: 27.02.2023	56142 US
Version:	10.0000	Issue date: 05.11.2022	Page 8 / 9

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

TSCA: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification	in section 3:	
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Acute Tox. 3 / H331	Acute toxicity (inhalative)	Toxic if inhaled.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]				
Acute Tox. 4	Acute toxicity (inhalative)	Calculation method.		
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.		
STOT SE 3	STOT-single exposure	Calculation method.		

Abbreviations and acronyms

Abbreviations and acronyms				
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road			
OEL	Occupational Exposure Limit Value			
BLV	Biological Limit Value			
CAS	Chemical Abstracts Service			
CLP	Classification, Labelling and Packaging			
CMR	Carcinogenic, Mutagenic and Reprotoxic			
DIN	German Institute for Standardization / German industrial standard			
DNEL	Derived No-Effect Level			
EAKV	European Waste Catalogue Directive			
EC	Effective Concentration			
EC	European Community			
EN	European Standard			
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations			
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk			
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous			
	Goods by Air			
IMDG Code	International Maritime Code for Dangerous Goods			
ISO	International Organization for Standardization			
LC	Lethal Concentration			
LD	Lethal Dose			
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships			
OECD	Organisation for Economic Cooperation and Development			
PBT	persistent, bioaccumulative, toxic			
PNEC	Predicted No Effect Concentration			
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals			
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail			
UN	United Nations			
VOC	Volatile Organic Compounds			
vPvB	very persistent and very bioaccumulative			
Eurther information				

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations.Without written approval, the product must not be used for purposes different from those mentioned in section



Article No.:	KW04000AHJ10	Classic Plus Reaktivvergütung	
Print date:	03.03.2023	Revision date: 27.02.2023	56142 US
Version:	10.0000	lssue date: 05.11.2022	Page 9 / 9

1.It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version