

Article Print o Versio	late:	KZ04000AAJ10 25.02.2023 9.0001	Brilliance OilCare Revision date: 25.0 Issue date: 18.11.2		56142 US Page 1 / 8
SEC	TION 1: Ide	entification of the	substance/mixtu	re and of the company	/undertaking
1.1.	Product ide	entifier			
		(manufacturer/supp e/designation	lier)	KZ04000AAJ10 Brilliance OilCare Stat. Warennummer 3405	52000
1.2.	Relevant ic	lentified uses of th	ne substance or mix	ture and uses advised ag	jainst
		lentified uses r paint related mate	rial		
	Do not use	ed against for injecting or spra not intended for con			
1.3.	Details of t	he supplier of the	safety data sheet		
	Berger-Seid	lle GmbH e - Klebstoffe - Bau aße 2	rter/downstream us	er/distributor) Telephone: +49 6359 / 80 Telefax: +49 6359 / 8005	
	Departmen	t responsible for i	nformation:		
	Laboratory E-mail			Sicherheitsdaten@berge	r-seidle.de
1.4.		r telephone numbe eraency number in		88271 or +11 49 700 2411	
SEC		zards identificat			
2.1.	Classificat	ion of the substan	ce or mixture		
	GHS-US cla	assification			
	Flam. Liq. 4	/ H227	Flammable liquids	C	Combustible liquid.
2.2.	Label elem				
	GHS-US la				
	Hazard pic	-			
	Warr Hazard sta	-			
	Hazaru sta H227		tible liquid.		
	P210 P280 P370 + P37 P403 P501	ary statements Keep av Wear pr 8 In case Store in	vay from heat, hot sur otective gloves and e of fire: Use extinguish a well-ventilated plac of contents/containe	eye/face protection. hing powder or sand to exti	
2.3.	Other haza		Ale uz viziele z video viziele Alie u		

Spontaneous ignition possible through autoxidation of cloths soaked in the product. (The same applies to dust and other paint-soaked items). The product itself is not self ignitive.

Other information

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

 Description
 Oils/waxes, high in solvents, aromatics removed

 Hazardous ingredients

GHS-US classification



rticle No.: rint date: ersion:	KZ04000AA 25.02.2023 9.0001	10 Brilliance OilCare Revision date: 25.02.2023 Issue date: 18.11.2022	56142 US Page 2 / 8	
CAS No		signation emark		weight-%
Α		anes, C11-13-isoalkane < 2% Aromaten		50 - 100
15956-5	58-8 2-e	thylhexanoic acid, manganese salt		0,25 - 0,5

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).



Article No.:	KZ04000AAJ10	Brilliance OilCare
Print date:	25.02.2023	Revision date: 25.02.2023
Version:	9.0001	Issue date: 18.11.2022

56142 US Page 3 / 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.



Print date: 25.02.2023 Revision date: 25.02.2023 Version: 9.0001 Issue date: 18.11.2022			
---	--	--	--

56142 US Page 4 / 8

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Physical state:	Liquid
	Colour:	amber
	Odour:	characteristic
	Odour threshold:	not applicable
	Initial boiling point and boiling range:	170 °C Source: Alkanes, C11-13-isoalkane < 2% Aromaten
	Lower and upper explosion limit:	
	Lower explosion limit:	0,6 Vol-%
	Upper explosion limit:	7 Vol-%
	-	Source: Alkanes, C11-13-isoalkane < 2% Aromaten
	Flash point:	62 °C
	Auto-ignition temperature:	> 200 °C Source: Alkanes. C11-13-isoalkane < 2% Aromaten
	Decomposition temperature:	not applicable
	pH at 20 °C:	not applicable
	Cinematic viscosity (40°C):	20 mm²/s
	Viscosity at 20 °C:	12 s 4 mm Method: DIN 53211
	Solubility(ies):	
	Water solubility at 20 °C:	insoluble
	Partition coefficient: n-octanol/water:	see section 12
	Vapour pressure at 20 °C:	0,4 mbar
		Method: calculated.
		Source: Alkanes, C11-13-isoalkane < 2% Aromaten
	Density and/or relative density: Density at 20 °C:	0.95 a/om3
	Density at 20°C.	0,85 g/cm³ Method: ISO 2811, part 3
	Relative vapour density:	not applicable
	particle characteristics:	not applicable
9.2.	Other information	not approache
0.2.	Solvent separation test:	< 3 weight-% (ADR/RID)
0=0		
SEC	TION 10: Stability and reactivity	

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable



56142 US Page 5 / 8

Article No.:	KZ04000AAJ10	Brilliance OilCare
Print date:	25.02.2023	Revision date: 25.02.2023
Version:	9.0001	Issue date: 18.11.2022
version.	5.0001	

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation; Serious eye damage/eye irritation

2-ethylhexanoic acid, manganese salt

Skin

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment



Article No.: Print date: Version:	KZ04000AAJ10 25.02.2023 9.0001	Brilliance OilCare Revision date: 25.02.2023 Issue date: 18.11.2022	56142 US Page 6 / 8	
The subs	stances in the mixture	do not meet the PBT/vPvB criteria	according to REACH, annex XIII.	
12.6. Endocrine disrupting properties No information available.				
12.7. Other adverse effects				

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

not applicable

not applicable

not applicable

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

14.2. UN proper shipping name

- 14.3. Transport hazard class(es)
- 14.4. Packing group

14.5. Environmental hazards

Land transport (ADR/RID)	not applicable
Marine pollutant	not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG)

EmS-No.

not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

US Federal regulations

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] This product is not classified according to Directive 2012/18/EU.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 542 VOC-value (in g/L) ASTM D2369: 542



Article No.:	KZ04000AAJ10	Brilliance OilCare		
Print date:	25.02.2023	Revision date: 25.02.2023	56142 US	
Version:	9.0001	Issue date: 18.11.2022	Page 7 / 8	

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

TSCA: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

	mation			
Full text of classification in section 3:				
Asp. Tox. 1 / H304		Aspiration hazard		May be fatal if swallowed and enters airways.
Eye Irrit. 2 / H319		Serious eye damage/eye irr	itation	Causes serious eye irritation.
Repr. 2 / H361		Reproductive toxicity		Suspected of damaging fertility or the unborn
1		1 5		child (state specific effect if known) (state route
				of exposure if it is conclusively proven that no
				other routes of exposure cause the hazard).
STOT RE 2 / H373		STOT-repeated exposure		May cause damage to organs (or state all
				organs affected, if known) through prolonged or
				repeated exposure (state route of exposure if it
				is conclusively proven that no other routes of
				exposure cause the hazard).
Aquatic Chronic 2 / H4	411	Hazardous to the aquatic er	nvironment	Toxic to aquatic life with long lasting effects.
Classification proce				
Classification for mixtu	ures and	used evaluation method acco	ording to regulati	ion (EC) No 1272/2008 [CLP]
Flam. Liq. 4		Flammable liquids		On basis of test data.
Abbreviations and a	cronyms	i		
ADR			International Ca	arriage of Dangerous Goods by Road
OEL		tional Exposure Limit Value		· - ·
BLV		al Limit Value		
CAS	Chemic	al Abstracts Service		
CLP	Classifie	cation, Labelling and Packagi	ng	
CMR	Carcino	genic, Mutagenic and Reprot	oxic	
DIN	Germar	Institute for Standardization	/ German indust	rial standard
DNEL		No-Effect Level		
EAKV		an Waste Catalogue Directive	;	
EC		e Concentration		
EC	-	an Community		
EN	•	an Standard	_	
IATA-DGR		ional Air Transport Associatio		
IBC Code				nt of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI			tion Technical li	nstructions for the Safe Transport of Dangerous
	Goods I			
IMDG Code		ional Maritime Code for Dang		
ISO		ional Organization for Standa	ruization	
LC	Lethal C	Concentration		
			Convention for H	he Provention of Pollution from Shine
MARPOL OECD				he Prevention of Pollution from Ships
PBT	-	ation for Economic Cooperati nt, bioaccumulative, toxic	ion and Develop	
PNEC		ed No Effect Concentration		
REACH		ation, Evaluation, Authorisatio	n and Restriction	n of Chemicals
RID		ions concerning the Internation		
UN	United I		nai Ganaye Ol	Dangerous Coous by Itali
VOC		Organic Compounds		
vec vPvB		sistent and very bioaccumula	ative	
Further information	701 y p01	sistem and very biodoodinuit		

Classification according to Regulation (EC) No 1272/2008 [CLP]



Article No.:	KZ04000AAJ10	Brilliance OilCare	
Print date:	25.02.2023	Revision date: 25.02.2023	56142 US
Version:	9.0001	Issue date: 18.11.2022	Page 8 / 8

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version