

AQUASEAL® ANTISLIP ADD

Description

AQUASEAL® ANTISLIP ADD is a surface structure generator on the basis of ceramics for AQUASEAL® NATURALWHITE, AQUASEAL® ROYALMAT, AQUASEAL® CERAMICSTAR, AQUASEAL® GREENSTAR, AQUASEAL® ELASTICSTAR and AQUASEAL® ECOGOLD (only AQUASEAL® CERAMICSTAR is described below also applies to the other finishes). One gets a high-abrasion resistant, highly chemicals resistant coating for high-traffic hardwood floors. AQUASEAL® CERAMICSTAR matt used together with AQUASEAL® ANTISLIP ADD meets the requirements of DIN 51130 with the anti-slip class R10 or R11, depending on the application.

Certificates / Approvals



AbZ-Nr.: Z-157.10-47
Slip resistance: DIN 51130/DGVU 108-003 R10/R11
ATFA: Compliant
NWFA: Compliant
MFMA: Compliant

Degree of gloss

Recommended as additive for the degree of gloss „matt“

Application

AQUASEAL® ANTISLIP ADD is carefully mixed into the finished AQUASEAL® CERAMICSTAR ready mixed (varnish + hardener + 10 min. rest time) shortly before use in a 1:25 ratio by weight. The ready material is to be used for immediate roller application. When applying the material do, from time to time, thoroughly mix so as to avoid sedimentation and a non-uniform surface structure look.

Keep in mind that the AQUASEAL® ANTISLIP ADD is used only in the last coat of the lacquer system! For this we recommend the BERGERTOOL MICROFIBER ROLL ULTRASLIM.

This results in a system recommendation for a three-coat system:

Coat 1:
roll AQUASEAL® CERAMICSTAR matt or other primers alternatives
Coat 2:
roll AQUASEAL® CERAMICSTAR matt
Coat 3:
roll AQUASEAL® CERAMICSTAR matt + AQUASEAL® ANTISLIP ADD

Drying

The same as advised for AQUASEAL® CERAMICSTAR.

Consumption

Depending on substrate and working method approx. 80-100 ml/m² (10-12 m²/l) of mixed AQUASEAL® CERAMICSTAR. Here 0.2.kg of AQUASEAL® ANTISLIP ADD are used per 5 l of CERAMICSTAR parent varnish and 0.5 l of hardener.

Packaging

0.2 kg (suitable for 5,5 l of AQUASEAL® CERAMICSTAR)

Storage / Transport

AQUASEAL® ANTISLIP ADD can be stored for at least 36 months if transported and stored in dry conditions.

General remark

Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used. The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußbodentechnik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General instruction of use of hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.