

AQUASEAL® RETARDER

Description

AQUASEAL® RETARDER is an additive for slowing down the reaction speed of Berger-Seidle AQUASEAL® water-based finishes and AQUASEAL® FLEXPRIMER. This product is recommended and useful for extremely dry and/or hot regions to normalize the finish's drying process. It helps to support a normal film building process.

Certificates / Approvals



ATFA: complies
NWFA: complies
MFMA: complies

Application

AQUASEAL® RETARDER has to be carefully mixed with AQUASEAL® water-based varnishes shortly before use in a maximum of 2%. With 2-component varnishes, ideally before the hardener. Then the AQUASEAL® water-based varnish is processed as described for the respective varnish.

Drying

Delays the drying of AQUASEAL® varnishes.

Consumption

A maximum of 2% AQUASEAL® RETARDER is added to the AQUASEAL® water-based varnish.

Storage / transport

Shelf life of original unopened packing min. 48 months provided that material is transported and stored at a cool and dry place protected from freezing.

General remark

Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used. The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußbodentechnik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.