

AQUASEAL® UV Plus

Description

AQUASEAL® UV PLUS is an additive that is added to water-based paints and protects wood from turning yellow caused by UV light. AQUASEAL® UV PLUS is particularly suitable for use on light-coloured wood.

Certificates/Approvals



ATFA:	Fulfilled
NWFA:	Fulfilled
MFMA:	Fulfilled

Application

AQUASEAL® UV PLUS is carefully admixed into our AQUASEAL® water-based paints shortly before use, maximum 2%. For 2K-paints, ideally before the hardener is introduced. The AQUASEAL® water-based paint is then processed further as described for the respective paint.

Drying

Drying the AQUASEAL® water-based paints does not change them.

Consumption

Maximum 2% AQUASEAL® UV PLUS is added to the AquSeal® water-based paints.

Storage / transportation

When transported and stored in a frost-proof, cool and dry place in the original, unopened container, it will usually have a shelf life of at least 6 months.

General remark

Before using this product, please read the usage instructions carefully. This Berger-Seidle product must be used by a person that is professionally qualified for parquet laying work as these instructions are intended for him or her. The activities must be carried out in accordance with the rules of the trade, the state of the art and valid standards and regulations of the country in which the product is used. The specifications of DIN 18356 "Parquet and wood paving work" and DIN 18365 "Floor covering work", information sheets as well as technical information from the TKB, the BEB, the CTA and the BVPF-Federal Association for Parquet & Flooring Technology must be followed and observed. The customer must be informed about cleaning and care instructions for the product. Any use that does not adhere to the area of application specified by Berger-Seidle is considered improper. Improper use and failure to follow the instructions in these respect are entirely under the responsibility of the worker and therefore exempt the manufacturer from liability and warranty obligations. Before using the product, general conditions for use must be verified accordingly and professionally.

Cross reference

The following sections of our datasheet collection are considered components of this datasheet:

- General information on the use of parquet sealing products
 - Cleaning and care for the sealed/oiled floor
 - Labelling and safety instructions (safety data sheet)
- * If the content of the technical data sheet differs from others printed matter such as labels, the latest version of the technical data sheet on the homepage is always valid. Printed matter is always adapted when reprinted.