Technical Data Sheet



BERGERBOND COLORADD P

Description

BERGERBOND COLORADD P is a color concentrate for the darker coloring of adhesives:

- BERGERBOND M1P
- BERGERBOND M1
- BERGERBOND M1X
- BERGERBOND P2S

Certificates / Approvals











ATFA: Compliant NWFA: Compliant MFMA: Compliant

Technical data

Mixing ratio:

Processing/laying time: Fit for walking on after: Fit for further work after: Final hardness after:

approx. 2-3 g COLORADD P per 1 kg (0.3-0.4 us fl oz/gal) of glue. for lighter woods less ColorAdd P can be used. as appropriate adhesive as appropriate adhesive as appropriate adhesive as appropriate adhesive

All data are based on standard climate (23°C and 50% rel. humidity).

If the conditions differ from this standard, the times will differ tool

Special notes

Do not use BERGERBOND COLORADD P and glue in conditions below +15°C or above 65% rel. humidity. In the cold season adhesive and flooring elements should be given time to reach the same temperature.

Mix well the components (min. 3 min.) with a suitable mixer. The mixing process is complete when a uniform color tone is achieved.

When drying, the adhesive darkens considerably. Sample production is recommended if exact coloring is desired.

After this process the adhesive can be evenly applied with an appropriate serrated trowel (BERGERTOOL ZAHNSPACHTEL B3, B7, B11, B15).

Immediately lay the flooring elements, thoroughly press.

Follow the structural components' extension joints.

Consumption

 $1-4 \text{ g/m}^2$ (0.3-0.4 us fl oz/gal), depending on trowel serration, flooring type, desired tone and subfloor.

The subfloor must be clean (free of contaminations), dry (permanently dry!), firm, plane and free of cracks. The requirements of DIN 18356 "Wood flooring works" or of DIN 18367 "Wood paving works", as appropriate, must be met.

If there is a risk of rising moisture, one has to check whether the relevant rules referring to the sealing against moisture have been complied with.

In case of underfloor heating or strongly absorbent surfaces such as anhydrite or magnesite screeds the subfloor should be primed with BERGERBOND PRIMER P. Ensure adequate drying of the primer.

Storage / transport

Can be stored for at least 12 months as from the date of production if transported and stored in cool and dry conditions, and if the original packaging is not opened. Protect from frost!

General remark

Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used. The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußbodentechnik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General recommendations for the usage of parquet and flooring adhesives
- Marking and safety recommendations (MSDS)
- Installation instructions by hardwood floor manufacturers and valid standards
- * If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made

Date of issue 11/2022 - Page 1 of 1