## Technical Data Sheet



# Brilliance Cleaner L94 Wachsentferner (Wax Remover)

BRILLIANCE CLEANER L94 is a basic cleaner removing dirty films of self-shining maintenance products resp. wax coats on finished hardwood and other wooden floors. Basic cleaning is necessary whenever maintenance films have taken up too much dirt and the floor has become unsightly.











Giscode: GU50 ATFA: Compliant NWFA: Compliant MFMA: Compliant

Attention: Do not soak the floor with water, otherwise the wood may be damaged by swelling. If Brilliance Cleaner L94 is left on the floor for too long, the finishing film may be damaged.

If a floor is damaged or the finishing film is worn through to the wood, penetrating water may have a greying effect on the wood. In this case the floor should be sanded completely and refinished in due time.

BRILLIANCE CLEANER L94 can be used both for basic cleaning and (strongly diluted with water) for intermediate cleaning.

The floor is moistened. BRILLIANCE CLEANER L94 is spread and scrubbed after a short waiting period either manually or by means of a machine. Depending on the extent of the soilings and the thickness of the film, BRILLIANCE CLEANER L94 is either used undiluted or mixed with water (mixing rate 1:1). If necessary, the cleaning procedure is repeated. The solved dirty film is removed and the floor is wiped with clear water.

Necessary if the surface is slightly dirty only. Approx. 300 ml of Brilliance Cleaner L94 is added to 10 l of water and the superficial dirt is removed by normal wet-cleaning.

The floor is moistened. BRILLIANCE CLEANER L94 is spread out and scrubbed manually or mechanically after a short exposure. Depending on the degree of soiling and the thickness of the care film, apply pure or 1: 1 diluted with water and repeat the cleaning process if necessary. The loosened dirt film must be taken up immediately. Afterwards, always wipe with clear water. After this intensive cleaning, further treatment with CLASSIC BASEOIL, BRILLIANCE FITPOLISH, BRILLIANCE OILCARE, CLASSIC 100PROOIL or BRILLIANCE SUPERWAX may be necessary. For a thorough cleaning with oil removal, we recommend Brilliance BioSoap or Brilliance **CLEANER L91** 

approx. 20 ml/m<sup>2</sup> or 50 m<sup>2</sup>/l (2000 sf/gal)

BRILLIANCE CLEANER L94 contains non-ionic tenside, additives, water soluble alcohols, solvents and fragrances, pH level: 6.

Shelf life of original unopened packing 24 months min. provided that material is transported and stored at a cool and dry place.

Please read the instructions carefully before processing this product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)
- \* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.

Date of issue 11/2022 Page 1 of 1