

BRILLIANCE EVERCLEAR

Description

BRILLIANCE EVERCLEAR is a water-based antiskid care product for finished parquet and hardwood flooring, finished cork (closed-porous) surfaces, PVC and linoleum. BRILLIANCE EVERCLEAR glänzend (glossy) complies with the sports floor certification according to DIN V 18032-2 and DIN EN 14904. We also have Brilliance Everclear matt in our portfolio.

BRILLIANCE EVERCLEAR should be used on floors with intact finish films only, otherwise the wood is liable to turn grey as a result of water penetration.

Certificates / Approvals



Giscode:	GE10
DIN V 18032-2:	Suitability for sports floors BRILLIANCE EVERCLEAR
DIN EN 14904:	Suitability for sports floors BRILLIANCE EVERCLEAR
ATFA:	Compliant
NWFA:	Compliant
MFMA:	Compliant

Note

As a rule, a finished floor should be treated with BRILLIANCE EVERCLEAR after 8-10 days only. The service life of the finish strongly depends on the careful treatment of the floor during the first days. Prior to the first intensive use at the latest, the floor must be treated as described under item „First and basic maintenance“. Depending on its use, every finish is subject to natural wear. For this reason, regular maintenance is absolutely essential. If the surface is damaged by use, the floor must be sanded completely and recoated. This measure is also part of the maintenance of finished floors and should be carried out in due time. Puddles should be avoided and saturated cloths or pads should not be left on the flooring in order to avoid discolorations.

Impregnated floors should be treated with Brilliance AQUASATINPOLISH, BRILLIANCE PFLEGEÖL or BRILLIANCE FITPOLISH as they are liable to turn grey due to water penetration. Basic cleaning is necessary whenever the maintenance system is changed.

Application

Shake well before use. BRILLIANCE EVERCLEAR can be used in two methods:

First and basic maintenance

The first coat of BRILLIANCE EVERCLEAR after finishing or after every basic cleaning is evenly and undiluted applied to the floor. Consumption: approx. 30-40 ml/m² (800-1400 sf/gal) (undiluted).

Use lintfree cloths or our special wiper BERGERTOOL CARE APPLICATOR for application.

Regular maintenance

For regular cleaning and care, 0,2–0,3 l of BRILLIANCE EVERCLEAR is added to about 8-10 l of water and the floor is wiped with a damp cloth or mop.

Basic cleaning

BRILLIANCE EVERCLEAR forms a film on the floor. Depending on the frequency and intensity of maintenance, the film must be removed either manually or by means of a machine using BRILLIANCE CLEANER L94 Wachsentrferner (wax-remover). Generally, basic cleaning is required whenever the floor is unsightly or heavily soiled with impurities which cannot be removed by normal cleaning.

Important note

Do not soak the floor with water during maintenance or basic cleaning as swelling of the wood may lead to damages.

Drying:

Fast drying, fully loadable immediately after drying.

Storage / transport

Shelf life of original unopened packing 24 months min. provided that material is transported and stored at a cool and dry place protected from freezing.

Industrial-coated prefinished hardwood floors

When used as a full care on engineered parquet and laminate, the liability must be checked on a case by case basis. Also, an edge protection with BRILLIANCE FILLANDFINISH may be required in advance. Observe the recommendations of the pre-finished parquet manufacturers.

General remark

Please read the instructions carefully before processing this product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.