

## SOLVSEAL UNIQUICKPRIMER

### Description

SOLVSEAL UNIQUICKPRIMER is an impregnating quickly drying plastic primer for roller or brush application based on alcohol. SOLVSEAL UNIQUICKPRIMER is suitable for most wood species and blocks wood extractives to a great extent. It is also effective in blocking wax residues contained in board joints of old floors. SOLVSEAL UNIQUICKPRIMER can be recoated with any of our solvent-based finishes as well as with most water-based AQUASEAL® finishes. SOLVSEAL UNIQUICKPRIMER preserves the natural colour of the wood.

### Certificates / Approvals



Giscode: G2

### Application

SOLVSEAL UNIQUICKPRIMER is applied rich and evenly in one coat by roller or brush. Problematic substrates should be coated with a flat brush in order to improve penetration. When used on highly absorbent species (eg beech), two coats of SOLVSEAL UNIQUICKPRIMER must be applied.

It is particularly important to ensure the sealer is applied uniformly to avoid light-dark discolouration developing after final coating.

### Drying

When the sealer is applied by roller or brush the drying time is approximately 45-60 min. per coat under normal conditions (15- 23°C/40-65% rel. humidity). With limited ventilation, low temperatures, high humidity or increased coat thickness, the drying may be delayed considerably.

Final coating with the permitted AquaSeal® water-based finishes can only be done after complete drying, otherwise appearance problems with the final coatings will occur. Drying overnight is recommended.

The product must be sealed within 24 h at the latest.

### Consumption

Depending on the wood surface and application method used, the application rate of 1 roller or brush coat is approximately:

110-120 ml/m<sup>2</sup> or 8-10 m<sup>2</sup>/l

With strongly absorbent species, a significantly higher consumption is to be expected.

### Storage / transport

Shelf life of original unopened packing min. 15 months provided that material is transported and stored at a cool and dry place.

### Restriction of use

SOLVSEAL UNIQUICKPRIMER should not be used for floors with extremely heavy traffic in conjunction with floor vibrating (e.g., sports floors).

### Safety Precautions

Highly flammable liquid and vapor. Causes serious eye irritation.

May cause drowsiness and dizziness. Keep away from heat, hot surfaces, sparks, open flames and other types of ignition sources. Do not smoke. In case of fire, use dry chemical powder or sand to extinguish. Store in a well-ventilated place. Keep container tightly closed and cool.

### General remark

Please read the instructions carefully before applying this product. This Berger-Seidle product must be applied by a qualified timber flooring contractor, for whom this information sheet is intended. The activities shall be carried out in accordance with the standards applicable to the trade, and regulations of the country in which the product is used. Any use that does not conform to of Berger-Seidle's application instructions is considered improper. The improper use and non-compliance with the instructions in this information sheet largely the responsibility of the person using the product, will void the manufacturer's liability and warranty. Before using the product, the general conditions for use must be thoroughly checked and understood.

### Cross reference

The following Technical Data Sheets should be read in conjunction with this data sheet:

- General instructions of use for hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (SDS)