

AQUACHOICE EXOBLOC TURBO

Product Description

AQUACHOICE EXOBLOC TURBO is the hardening component for the high-quality sealer AQUACHOICE EXOBLOC. It accelerates the overcoatability of CLASSIC EXPRESSSTAINS to 2-3 h at all shades.

Certificates / Approvals



ATFA: Compliant Product
MFMA: Compliant Product
ATFA: Compliant Product

Specifications

Components: oligomeric isocyanate, according MSDS
Clarity: clear
Scent: unoffensive
Body: viscous liquid
Texture: smooth
Density: 8.51 lb/gal
Packaging: 13oz
Sheen: n.a.
Coverage: n.a. see basic system
Stability: do not freeze
Leveling: n.a.
Defoaming: n.a.
Drying Time: n.a. see basic system
Pot Life: 2 hrs.
Cure Time: n.a. see basic system
Chemical Resistance: n.a.
Shelf Life: 1 year unopened
Flash Point: n.a.

For further details please refer to MSDS.

Application Instructions

For professional use only.

Shake well before use. Prior to the application AQUACHOICE EXOBLOC IS MIXED WITH AQUACHOICE EXOBLOC TURBO (MIXING RATIO 10:1) in a bucket or container. The pot life (usability) of the mixture is approximately 2 hours. Only mix the quantity required for application. The finish mixture emits carbon dioxide, which must not be sealed in an airtight container to avoid bursting. Classic ExpressStain should be allowed to dry 2-3 h before the use of AQUACHOICE EXOBLOC WITH AQUACHOICE EXOBLOC TURBO. It can be applied by roller, brush or T-bar applicator. Use clean tools. Apply in one uniform coat with care being taken to apply in the direction of the wood grain. With rich coats, allow for penetration into joints and cracks. Avoid irregular application of the sealer.

Do not apply AQUACHOICE EXOBLOC with AQUACHOICE EXOBLOC TURBO at temperatures below 55° F. Use water for tool clean-up immediately after finishing.

A sufficient dry can be obtained within 2-3 hours with a constant temperature of 70° F and 50% relative air humidity.

Prior to the next coat, the surface must be uniformly dry. Insufficient ventilation, lower temperatures, increased coat thickness and erratic air humidity may prolong sufficient drying. Under optimal conditions, the stain, sealer and a layer of the desired finish can be applied in one day.

AQUACHOICE EXOBLOC with AQUACHOICE EXOBLOC TURBO can be coated with all AQUACHOICE products. The first layer of topcoat should dry overnight.

Maintenance and Care

Regular cleaning and care with compatible care products is essential for extended floor life and beauty. For best results, use BRILLIANCE CLEANER L94 for basic cleaning and tough stain removal. We recommend the installation of floor mats at each entry to keep out undue dirt, mud and grit.

System Recommendations

Do not use AQUACHOICE EXOBLOC TURBO in combination with other 'liquid/wet' sealers or finishes.

AquaChoice ExoBloc Turbo has a shelf life of 1 year from production date.

Safety Precautions

May cause skin and eye irritation. May be harmful if swallowed. May cause an allergic reaction. Avoid skin or eye contact and inhalation of vapors. Use with adequate ventilation. Wash thoroughly after handling. Keep unmixed containers closed. Do not seal containers containing mixed product due to release of carbon dioxide.

Do not use for sputtering or spraying. Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

Description of first aid measures

If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +1 872 5888271

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

AQUACHOICE EXOBLOC TURBO

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper.

The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)

*If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.