Technical Data Sheet

Berger-Seidle
Parkett will das Beste!

AquaChoice LevelGel

Description
AquaChoice LevelGel is a quickly drying gel-like trowel compound based on water-thinnable acrylate polyurethane dispersions. AquaChoice LevelGel is almost odourless, inflammable and suitable as intermediate coat for our water-based AquaChoice finishes. Please refer to the individual Technical Data Sheets of the finishes.
The gel-like consistency of the material achieves closed surfaces and covers small joints resulting in an excellent filling capacity and a brilliant visual effect. Compared with finishes, the drying time of AquaChoice LevelGel can quickly be sealed over.

Certificates / Approvals

Giscode: W2+
AbZ-Nr. AbZ-approved
ATFA: Compliant
NWFA: Compliant
MFMA: Compliant

Specifications

Components:	waterbased dispersions, according MSDS
Clarity:	translucent, dries clear
Scent:	unoffensive – amine
Body:	full
Texture:	richly smooth
Density:	8.91 lb/gal
Packaging:	1 gal
Coverage:	2200 – 2500 sf/gal
Stability:	do not freeze
Leveling:	excellent
Defoaming:	excellent
Drying Time:	30 – 60 min
Shelf Life:	15 months unopened
Flash Point:	N / A

For further details please refer to MSDS.

Application
The material is applied as an interlayer in 2 cross-trowel coats, normally after the intermediate sanding of the second coat of varnish. After drying, the surface is recoated without screening. The working method must be adjusted to the use of the floor.

Drying
Standard climate 73° F/50% rel. humidity: Surface can be recoated after approx. 30–60 min. Insufficient ventilation, low temperatures, high humidity or increased coat thickness may delay drying considerably. Prior to recoating, the surface must be sufficiently dry.

Storage / transport
Shelf life of original unopened packing 15 months min. provided that material is transported and stored at a cool and dry place protected from freezing.

Safety Precautions
Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

Description of first aid measures
If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +1 872 5888271

General information
In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation
Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact
Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact
Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion
If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed
In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed
First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations
This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you

Berger-Seidle America LP • www.berger-seidle.com • info@berger-seidle.com • Tel: 770.295.2282

AquaChoice LevelGel

cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed.

The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper.

The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Identification and safety instructions (MSDS)

**If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.

Berger-Seidle America LP • www.berger-seidle.com • info@berger-seidle.com • Tel: 770.295.2282