

AQUACHOICE SPORT B

Technical Data Sheet



Berger-Seidle



AquaChoice SPORT B COLOR LinePaint

Product Description

AQUACHOICE SPORT B COLOR LINEPAINT is a highly elastic one-component waterborne wood floor paint which is used for marking lines on hardwood floorings in sports halls.

Certificates / Approvals



Giscode: W3+
ATFA: Compliant
NWFA: Compliant
MFMA: Compliant

Specifications

Components: waterbased dispersions, according MSDS
Clarity: colored
Scent: unoffensive
Body: moderate
Texture: liquid
Packaging: 1 gal [3,79l]
Coverage: 350-550 sf/gal [100ml/m² or 10m²/l]
Stability: do not freeze
Leveling: excellent
Defoaming: excellent
Dry Time: 12 hrs.
Cure Time: 8 – 14 days, depending on climate conditions

Chemical
Resistance: N / A
Shelf Life: 15 months unopened
Flash Point: N / A

For further details please refer to MSDS.

Application Instructions

AQUACHOICE SPORT B LINEPAINT can be applied by roller or brush. Use clean tools. AquaChoice SPORT B COLOR LINEPAINT can be applied between AQUACHOICE SPORT B TWO according to the following built-up:

- Apply one coat of AQUACHOICE SealUp
- Apply one coat of AQUACHOICE SPORT B TWO
- SCREEN THOROUGHLY WITH GRIT 180
- Vacuum thoroughly
- APPLY AQUACHOICE SPORT B COLOR LINEPAINT. More than one coat may be needed. Apply second coat when first coat is dry to touch
- Drying time of 24 h
- SCREEN THOROUGHLY AQUACHOICE SPORT B COLOR LINEPAINT WITH MAROON PAD
- Vacuum thoroughly
- APPLY 1-2 COATS OF AQUACHOICE SPORT B TWO

Processing instructions for the different products can be found in the corresponding TDS.

Screening thoroughly is essential for good adhesion. Use new screens in time.

Other built-ups have to be discussed with our application engineers.

Drying

The varnish can generally be abraded after 24 h (73,4°F [20°C] / 50% relative humidity). With poor ventilation, lower temperature, other air humidity and increased layer thickness drying can be significantly delayed.

Consumption

Depending on method

1 roll/paint coat:
0.31 us fl oz/sq ft resp. abt. 350-550 sf /gal
[100ml/m² or 10m²/l]

Safety Precautions

Do not use for sputtering or spraying. Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

Description of first aid measures

If medical advice is needed, have product container or label at hand.
24-hour emergency number in side USA: +1 872 5888271

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

AQUACHOICE SPORT B^T

Technical Data Sheet



Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed.

The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Identification and safety instructions (MSDS)

**If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed

valid. Printed material is always adapted when reprints are made.