# AquaChoice SPORT Retarder

### **Product Description**

AQUACHOICE SPORT B RETARDER is an additive for slowing down the reaction speed of Berger-Seidle AQUACHOICE water-based finishes. This product is recommended and useful for extremely dry and/or hot regions to normalize the finish's drying process. It helps to support a normal film building process.

### Certificates / Approvals











ATFA: Compliant NWFA: Compliant Compliant MFMA

### **Specifications**

Components: solvents, according MSDS

Clarity: clear Scent: unoffensive Bodu: moderate Texture: liquid

Packaging: 0.4 us fl qt [371ml] Coverage: same as varnish Stability: do not freeze Leveling: excellent Defoaming: excellent Dry Time: N/A N/A

Cure Time: Chemical

N/AResistance:

Shelf Life: 48 months unopened

Flash Point: N/A

For further details please refer to MSDS.

### **Application Instructions**

AQUACHOICE SPORT B RETARDER has to be carefully mixed with AQUACHOICE SPORT B water-based shortly before use in a maximum of 2%. In the case of 2-component coatings, ideally before the hardener. Then the AQUACHOICE SPORT B waterbased varnish is processed as described for the respective varnish.

Delays the drying of AQUACHOICE SPORT B varnishes.

## Consumption

A maximum of 2% AQUACHOICE SPORT B RETARDER is added to the AQUACHOICE SPORT B water-based varnish.

### Storage / transport

Shelf life of original unopened packing min. 48 months provided that material is transported and stored at a cool and dry place protected from freezing.

### Safety Precautions

Do not use for sputtering or spraying. Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

### Description of first aid measures

If medical advice is needed, have product container or label at

24-hour emergency number in side USA: +1 872 5888271

### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

### Most important symptoms and effects, both acute and delaued

In all cases of doubt, or when symptoms persist, seek medical advice.

### Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish

# AQUACHOICE SPORT B Technical Data Sheet

any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed.

The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

### Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Identification and safety instructions (MSDS)

\*\*If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.

Berger-Seidle