

## BERGERBOND COLORADD D

### Description

BERGERBOND COLORADD D is a color concentrate designed to darken the color of BERGERBOND D1.

### Certificates / Approvals



ATFA: Compliant  
NWFA: Compliant  
MFMA: Compliant

### Technical data

Mixing ratio: approx. 3–5 g COLORADD D per 1 kg (0.4-0.7 us fl oz/gal) of glue. For lighter woods less ColorAdd D can be used.

All data is based on a standard climate (73°F and 50% rel. humidity).

If the conditions differ from this standard, the times will differ too!

### Specifications

Components: color paste, according MSDS  
Clarity: dark brown  
Scent: mild  
Density: 1,69 g/l (14,10 lb/gal)  
Packaging: 0,5 l (0,13 gal)  
Stability: do not freeze  
Drying Time: same as adhesive  
Pot Life: same as adhesive  
Shelf Life: 1 year unopened  
Flash Point: N / A

### Special notes

Do not use BERGERBOND COLORADD D and adhesive in conditions below 59°F or above 65% rel. humidity. In the cold season, adhesive and flooring elements should be given time to reach the same temperature.

### Application

Mix the components well (min. 3 min.) with a suitable mixer. The mixing process is complete when a uniform color tone is achieved.

When drying, the adhesive darkens considerably. Sample production is recommended if exact coloring is desired.

After this process the adhesive can be evenly applied with an appropriate serrated trowel (BERGERTOOL TOOTHED TROWEL B3, B7, B11, B15).

Immediately lay the flooring elements, thoroughly press.

Follow the structural components extension joints.

Date of issue 11/2022- Page 1 of 2

### Storage / transport

Can be stored for at least 12 months from the date of production if transported and stored in cool and dry conditions, in unopened packaging. Keep from freezing!

### Safety Precautions

May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Precautionary statements. Avoid breathing vapours. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves and eye/face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before wearing again. Dispose of contents/container to industrial incineration plant.

### Description of first aid measures

24-hour emergency number in side USA: +1 872 5888271

### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

### Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## BERGERBOND COLORADD D

### Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

### Cross reference

The following Technical Data Sheets should be observed:

- General recommendations for the usage of hardwood flooring adhesives
- Marking and safety recommendations (MSDS)

Installation instructions by hardwood flooring manufacturers and valid standards

\* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.