

BRILLIANCE AQUASATINPOLISH

Description

BRILLIANCE AQUASATINPOLISH is a colorless water-based semi-synthetic maintenance product containing wax for oiled and waxed parquet and hardwood floors. It is an extremely efficient care product and can be buffed after application

Sensitive and very absorptive wood species must not be flooded with BRILLIANCE AQUASATINPOLISH. Sparingly apply a uniform coat, otherwise the joints of the floor may be damaged. Avoid puddles and do not leave any soaked cloths or pads on the floor in order to avoid stains.

Certificates / Approvals



Giscode: GE10
ATFA: Compliant
NWFA: Compliant
MFMA: Compliant

Specifications

Components: Water, waxes, perfume, according MSDS
Clarity: Whitish emulsion
Scent: Mild
Body: Light liquid
Texture: Water-like
Density: 8.35 lb/gal
Packaging: 33.8 us fl oz
Sheen: N/A
Coverage: 1000-1400 sf/gal
Stability: Do not freeze
Leveling: N/A
Defoaming: N/A
Dry Time: Like water
Cure Time: N/A
Chemical Resist: N/A
Shelf Life: 2 years unopened
Flash Point: N/A

For further details please refer to MSDS.

Application Instructions

Shake well before use. The surface to be treated must be completely clean. Parquet and other wooden floors are cleaned using a mop, soft broom, vacuum cleaner or a damp cloth. Heel marks and stains are removed using BRILLIANCE CLEANER L94 or BRILLIANCE CLEANER L91 and a soft cloth. Do not use any steel wool, steel chips or any other abrasive tools. Do not flood the floor during maintenance or basic cleaning in order to avoid damages due to swelling of the wood. After cleaning, the surface is wiped with clear water.

First and basic maintenance

For basic maintenance, BRILLIANCE AQUASATINPOLISH is applied in a thin uniform layer by means of an applicator or a soft cloth. If the surface looks non-uniform, for example, in case of

Date of issue 11/2022 Page 1 of 1

insufficient wetting, the area can be equalized using a white pad after the maintenance film has dried.

Regular maintenance

For regular cleaning and care, abt. half a cup of BRILLIANCE AQUASATINPOLISH is added to abt. 2 gall. of water and the floor is wiped with a damp cloth.

Basic cleaning

For slight soiling, such as heel marks, grease, stains etc., a soft cloth is moistened with our water-based BRILLIANCE CLEANER L94 or BRILLIANCE CLEANER L91 and the soiled area is gently rubbed. In case of large surfaces, BRILLIANCE CLEANER L91 or BRILLIANCE CLEANER L94 is be sprayed on the floor and the surface is treated with a buffer and a white pad. Afterwards, the floor is wiped with clear water in order to remove the dissolved care film.

Important note

Do not flood the floor during maintenance or basic cleaning in order to avoid damages due to swelling of the wood. After cleaning, the surface is wiped with clear water.

Consumption

Depending on substrate and working method:
approx. 30-40 ml/m² (1000-1400 sf/gal)

Drying:

Fast drying, fully loadable immediately after drying.

Storage / transport

Shelf life of original unopened packing 24 months min. provided that material is transported and stored at a cool and dry place protected from freezing.

Safety Precautions

Do not use for sputtering or spraying. Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

Description of first aid measures

If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +1 872 5888271

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

BRILLIANCE AQUASATINPOLISH

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty.

Before using the product, the general conditions for use must be checked properly and professionally.

References

The following sections of our information pages are integral parts of this information sheet:

- General information about how to use parquet sealing products
- Cleaning and care of the sealed/oiled floor
- Labelling and safety information (safety data sheet)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.