Technical Data Sheet



BRILLIANCE CLEANER L94

Product Description

BRILLIANCE CLEANER L94 is a neutral pH waterborne floor cleaner developed for the removal of tough dirt, stains, selfshining films and some wax coats on finished hardwood and other type floors.

Certificates / Approvals



Giscode: GU50 ATFA: Compliant NWFA: Compliant MFMA: Compliant

Specifications

Water, solvent, according MSDS
Colorless
Lemon
Light liquid
Water-like
8.43 lb/gal
33.8 us fl oz
N/A
2000 sf/gal
Do not freeze
N/A
N/A
<1/2 hr.
N/A
N/A
2 years unopened
N/A
s please refer to MSDS.

Application Instructions

1. Basic Cleaning for sealed surfaces:

First, the floor is moistened with water. BRILLIANCE CLEANER L94 is spread uniformly over the floor and allowed to sit for about 5 minutes diluted at a ratio of approximately 2:1 water to BRILLIANCE CLEANER L94. Depending on the amount of dirt or the thickness of film to be removed, the floor may require scrubbing either manually or mechanically. If necessary, the procedure can be repeated. As dirt, stains and care films are dissolved, the floor should be wiped with a damp cloth. For extremely difficult dirt and stain removal, use full strength. For unknown substrates pretest at not direct visible spot.

Caution: Floor should not be soaked with water, which could result in swelling of wood.

2. Intermediate Cleaning for sealed and oiled surfaces: For daily or regular floor care to remove surface dirt, floor should be wiped with a damp cloth with a 5% ($\frac{1}{2}$ cup) solution of cleaner to 1 gallon of water.

Intensive cleaning for oiled surfaces

The floor is moistened. BRILLIANCE CLEANER L94 is spread out and scrubbed manually or mechanically after a short exposure. Depending on the degree of soiling and the thickness of the care film, apply pure or 1: 1 diluted with water and repeat the cleaning process if necessary.

The loosened dirt film must be taken up immediately. Afterwards, always wipe with clear water. After this intensive cleaning, further treatment with CLASSIC BASEOIL, BRILLIANCE FITPOLISH, BRILLIANCE OILCARE, CLASSIC 100PROOIL or BRILLIANCE SUPERWAX may be necessary. For deep cleaning with oil removal, we recommend BRILLIANCE BIOSOAP or BRILLIANCE CLEANER L91.

Maintenance and Care

Regular cleaning and care with compatible care products is essential for extended floor life and beauty. If a floor is damaged and/or the finish coat is worn through to the wood, cleaning water may penetrate and have a greying effect on the wood. In this case, the floor should be sanded and refinished as soon as possible. Use BRILLIANCE CLEANER L94 for basic cleaning and tough stain removal. Before allowing traffic, use BRILLIANCE EVERCLEAR for regular maintenance and a self-shining, non-slip floor.

System Recommendations

With tough dirt, stains and film build-up, use BRILLIANCE CLEANER L94 full strength or diluted. BRILLIANCE EVERCLEAR should be used as a floor care system on all Berger-Seidle System finishes after they have been fully cured and before traffic is allowed on the floor.

Description of first aid measures

If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +1 872 5888271

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Date of issue 11/2022 Page 1 of 1

Technical Data Sheet



BRILLIANCE CLEANER L94

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

References

The following sections of our information pages are integral parts of this information sheet:

- General information about how to use parquet sealing products
- Cleaning and care of the sealed/oiled floor
- Labelling and safety information (safety data sheet)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.

Date of issue 11/2022 Page 1 of 1