

CLASSIC EXPRESSSTAIN COLOR

Application Instructions

- Sanding and preparation of the surface to be stained must be done so according to accepted industry standards. Avoid sanding errors and ensure the complete removal of any old coatings or treatments. If necessary, AQUACHOICE® POWERFILLER AQUACHOICE® PAFUKIPOWDER COLOR or SOLVSEAL® PAFUKISUPER should be used for joint filling prior to final sanding. Following the final sanding, vacuum and tack the floor well to remove all dust.
- Water popping the wood surface before staining results in deeper penetration and a more uniform surface appearance. Following water pretreatment, verify the surface is dry with a moisture meter. Do not proceed with staining until readings match levels prior to pretreatment.
- After sanding and preparing the surface, Classic ExpressStain is applied with a brush, trim pad, soft towels, or carpet pad driven by a buffer.
- Allow 2-3 minutes of penetration
- Remove excess by hand wiping or buffing off with an absorbent, non-abrasive material.
- After the recommended drying time (see notes in Drying) Classic ExpressStain is overcoated with one of the recommended high-quality AquaChoice® or SolvSeal products within 48 hours of stain application.
- Tools can be cleaned with BRILLIANCE CLEANER L91

Maintenance and Care

As Classic ExpressStain is overcoated, please follow the Maintenance and Care Instructions for the corresponding varnish.

Safety Precautions

Soaked rags, pads and other working material as well as oil/wax in connection with sanding dust or the like must be moistened with water or deposited in a metal container to be disposed of in a safe way (danger of auto-ignition). The product itself is not self-igniting. Please pay regard to our Technical Special Information No. 17!

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves and eye/face protection. In case of fire: Use extinguishing powder or sand to extinguish. Store in a well-ventilated place not exceeding 100°F (38°C). Dispose of contents/container to industrial incineration plant.

Do not use for sputtering or spraying. Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

Description of first aid measures

If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +11 49 700 24112112

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Stand 06/2023 - Seite 2 von 3

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice. **Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been

avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFPA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußbodentechnik must be observed.

The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper.

The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and

CLASSIC EXPRESSSTAIN COLOR

as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

References

The following sections of our information pages are integral parts of this information sheet:

- General information about how to use parquet sealing products
- Cleaning and care of the sealed/oiled floor
- Labelling and safety information (safety data sheet)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.