CLEANCHOICE SPORT B Daily Clean

Product Description

CLEANCHOICE SPORT B DAILY CLEAN is a cleaning agent to be added to water for damp wiping of finished and oiled hardwood flooring. It is also suitable for other floors, doors, window frames and plastic surfaces. The product is available as a concentrate.

Certificates / Approvals











Giscode: GU50 (concentrate)

ATFA: Compliant NWFA: Compliant MFMA: Compliant

Specifications

Components: according MSDS
Clarity: Colorless
Scent: Lemon
Rodu: Light liquid

Body: Light liquid Texture: Water-like

Density: 8,26 lb/gal [0,997 g/cm³]

Packaging: 5 gal [18,97 l]

Sheen: N/A

Coverage: $2000 \text{ sf/gal } [20 \text{ ml/m}^2 \text{ or } 50 \text{ m}^2/\text{l}]$

Stability: do not freeze

Levelling: N/A
Defoaming: N/A
Dry Time: water
Cure Time: N/A
Chemical Resist: N/A

Shelf Life: 2 years unopened

Flash Point: N/A

For further details please refer to MSDS.

Application Instructions

Used as additive to wiping water for regular maintenance: Remove dirt using a broom or vacuum cleaner. Mix half a cup of CLEANCHOICE SPORT B DAILY CLEAN with abt. 5 qt. of warm water. Damp wipes the floor.

Carefully remove sticky dirt with a white pad and cleaning solution with a higher concentration.

Maintenance and Care

Regular cleaning and care with compatible care products is essential for extended floor life and beauty. If a floor is damaged and/or the finish coat is worn through to the wood, cleaning water may penetrate and have a greying effect on the wood. In this case, the floor should be sanded and refinished as soon as possible. Use CLEANCHOICE SPORT B POWER CLEAN for basic cleaning and tough stain removal. Before allowing traffic, use

VOC-free Brilliance Everclear cleaner for regular maintenance and a self-shining, non-slip floor.

System Recommendations

With tough dirt, stains and film build-up, use CLEANCHOICE SPORT B POWER CLEAN full strength or diluted. BRILLIANCE EVERCLEAR should be used as a floor care system on all Berger-Seidle System finishes after they have been fully cured and before traffic is allowed on the floor.

Safety Precautions

Harmful to aquatic organisms. Avoid release to the environment. Dispose of contents/container to industrial incineration plant.

Description of first aid measures

If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +1 872 5888271

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed.

The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Identification and safety instructions (MSDS)

**If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.