

# AQUA CHOICE SPORT B

## Technical Data Sheet



## CLEANCHOICE SPORT B Mineral Spirits

### Product Description

CLEANCHOICE SPORT B MINERAL SPIRITS is a solvent-based basic cleaner with a high cleaning effect for stains and heel marks as well as for the removal of dirty wax films on finished parquet, hardwood floors and other solvent-resistant surfaces.

### Certificates / Approvals



Giscode: GH10  
ATFA: Compliant  
NWFA: Compliant  
MFMA: Compliant

### Specifications

Components: solvents, according MSDS  
Clarity: Colorless  
Scent: Strong solvent  
Body: Light liquid  
Texture: Water-like  
Density: 6,34 lb/gal [0,758 g/cm<sup>3</sup>]  
Packaging: 5 gal [18,97 l]  
Sheen: N/A  
Coverage: 2000 sf/gal [20 ml/m<sup>2</sup> or 50 m<sup>2</sup>/l]  
Stability: N/A  
Leveling: N/A  
Defoaming: N/A  
Dry Time: <1/2 hr.  
Cure Time: N/A  
Chemical Resist: N/A  
Shelf Life: 3 years unopened  
Flash Point: 75°F

For further details please refer to MSDS.

### Note

Use CLEANCHOICE SPORT B POWER CLEAN for basic cleaning of floors treated with BRILLIANCE EVERCLEAR.

### Application Instructions

A cloth is soaked with CLEANCHOICE SPORT B MINERAL SPIRITS and the floor to be cleaned is scrubbed by machine or manually in sections. After a short waiting period, the dissolved wax film is wiped up with a dry cloth. Always use a fresh cloth so that the wax film is not spread but absorbed by the cloth. Depending on the extent of the soilings and the thickness of the film to be removed the cleaning procedure is repeated. Please see to it that no puddles of CLEANCHOICE SPORT B MINERAL SPIRITS remain on the finished floor. Soilings such as rubber marks, grease and colour stains are removed by rubbing with a soft cloth soaked with CLEANCHOICE SPORT B MINERAL SPIRITS.

CLEANCHOICE SPORT B MINERAL SPIRITS is a basic cleaner suitable for floors treated with wax-containing care products

(BRILLIANCE AQUASATINPOLISH and floors treated with CLASSIC BASEOIL, CLASSIC BASEOIL COLOR and CLASSIC 100 PROOIL). After careful cleaning with CLEANCHOICE SPORT B MINERAL SPIRITS one of our compatible maintenance or CLASSIC OIL products is applied immediately.

### Regular Cleaning:

For daily or regular floor care to remove surface dirt, floor should be wiped with a damp cloth with CLEANCHOICE SPORT B DAILY CLEAN.

### Maintenance and Care

Regular cleaning and care with compatible care products is essential for extended floor life and beauty. If a floor is damaged and/or the finish coat is worn through to the wood, cleaning water may penetrate and have a greying effect on the wood. In this case, the floor should be sanded and refinished as soon as possible. Use CLEANCHOICE SPORT B MINERAL SPIRITS for basic cleaning and tough stain removal. Before allowing traffic, use BRILLIANCE AQUASATINPOLISH for regular maintenance.

### System Recommendations

With tough dirt, stains and film build-up, use CLEANCHOICE SPORT B MINERAL SPIRITS full strength or diluted.

### Safety Precautions

Flammable liquid and vapour. Causes mild skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof electrical equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapours. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves and eye/face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER or doctor/physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. In case of fire: Use extinguishing powder or sand to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep locked up.

Dispose of contents/container to industrial incineration plant. Do not use for sputtering or spraying. Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

### Description of first aid measures

If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +1 872 5888271

# AQUA CHOICE SPORT B<sup>T</sup>

## Technical Data Sheet



### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

### Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed.

The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

### Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Identification and safety instructions (MSDS)

\*\*If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.