

SOLVSEAL PAFUKISUPER

Product Description

SOLVSEAL PAFUKISUPER is a colorless, solvent-based wood floor filler, developed for use with fine sanding dust from the parent floor to achieve an exact wood color match for trowel filling joints, cracks, gaps, nail holes and other cavities of any species of wood. After proper ratio mixing, the resulting filler material spreads very smoothly while achieving a fast dry. SOLVSEAL PAFUKISUPER may be used with waterborne, oil-modified, acid-cure and moisture-cure finishes.

Certificates / Approvals



ATFA:	Compliant
NWFA:	Compliant
MFMA:	Compliant

Specifications

Components:	according MSDS
Clarity:	clear
Scent:	strong solvent
Body:	moderately thick
Texture:	light gel
Density:	7.54 lb/gal
Packaging:	5 ltr.
Sheen:	N/A
Solid content:	13%
Coverage:	700-900 sf./gal.
Stability:	excellent
Leveling:	N/A
Defoaming:	N/A
Dry time:	20-30 minutes
Cure time:	N/A
Chem. resist:	N/A
Shelf life:	1 year unopened
Flash point:	39° F

For further details please refer to MSDS.

Application Instructions

SOLVSEAL PAFUKISUPER is best used when applied on the next to last cut with the sander. At this time, the surface to be filled must be completely clean and dry. SOLVSEAL PAFUKISUPER is mixed at approximately 2 parts of filler to 1 part of sanding dust by volume with clean, dry fine edger dust (80-100 grit is recommended) from the parent wood floor. After mixing for several minutes, SOLVSEAL PAFUKISUPER will develop into an ultra-smooth texture putty which must be applied with a trowel (our BERGER TOOL TROWEL is recommended). Work should proceed quickly to avoid residual cured material left on the surface. Large, deep cavities may need to be filled in more than one application. Product can be stored in its own container. After sufficiently dry, final sanding cut must be done to obtain a smooth surface. Residual dry putty onto the wood is to be sanded out properly. All tools should be cleaned immediately after use (we recommend lacquer thinner).

Date of issue 11/2022 Page 1 of 1

Insufficient ventilation, lower temperatures, increased coat thickness or erratic air humidity may delay drying considerably.

System Recommendations

For optimum results, and a brilliant effect on the floor, we recommend the complete Berger-Seidle System: All 1 and 2 component water-based finishes and maintenance products of the current Berger-Seidle product-range.

SOLVSEAL PAFUKISUPER has a 15 months shelf life from production date.

Safety Precautions

Highly flammable liquid and vapor. Causes mild skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof electrical equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Call a POISON CENTER or doctor/physician if you feel unwell. skin irritation occurs: Get medical advice/attention. In case of fire: Use extinguishing powder or sand to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep locked up. Dispose of contents/container to industrial incineration plant.

Do not use for sputtering or spraying. Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

Description of first aid measures

If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +1 49 700 2412112

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

SOLVSEAL PAFUKISUPER

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVVPF-Bundesverband Parkett & Fußbodentechnik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general

conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.