

## AQUASEAL® ECOSILVER

### Description

AQUASEAL® ECOSILVER is a hardwood floor finish for normal to medium traffic with a good price-performance ratio. Formulated on high-quality acrylate and polyurethane dispersions, the one-component water-based finish offers good properties within the sector of hardwood floor finishes favourable in price. One-component, ready for use and easy to apply.

Giscode: W3+

Emicode: EC1, abZ-Nr. 157.10-46

### Degree of gloss

ultramatt, matt, semigloss

### Special instructions

In general, AQUASEAL® ECOSILVER has a good adhesion on different substrates, for example, AQUASEAL® FLEXPRIMER, AQUASEAL® EXOBLOC and AQUASEAL® UNISPACHTEL.

### Application

AQUASEAL® ECOSILVER can be applied by roller, brush or cross-troweled. It is applied uniformly in three coats. Problematic wood species, such as beech, maple and ash, must not be troweled but roller-coated!

### Special advice

Contrary to conventional solvent-based finishes, AQUASEAL® ECOSILVER should be applied in rich layers. The material should not be excessively spread with the roller.

### Drying

In order to avoid excessive swelling pressure we recommend to apply only one coat by roller a day, so that the wood has enough time to set free again the water absorbed. In general the lacquer can be worked on and cautiously walked on after 3 to 4 hours. Standard climate 23°C 50% rel. humidity. Bad ventilation, low temperatures, different humidity or thick coats may delay drying considerably. Do not expose to wear, cover with carpets or apply care products for 8-14 days.

### Consumption

Depending on substrate and method:

1 trowel coat:

approx. 30 ml/m<sup>2</sup> resp. approx. 35 m<sup>2</sup>/l

1 roller/brush coat:

approx. 100 ml/m<sup>2</sup> resp. approx. 10 m<sup>2</sup>/l

### Storage / transport

Shelf life of original unopened packing min. 12 months provided that material is transported and stored at a cool and dry place protected from freezing.

### Industrial coated prefinished hardwood floors

AQUASEAL® ECOSILVER is not suitable for recoating of prefinished hardwood floors nor for cork.

### Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)