

AQUASEAL® SMARTHOME

Description

AQUASEAL® SMARTHOME is a one-component, quick-dry hardwood-floor lacquer. It is designed for coating hardwood and wood floors in apartments, with normal and medium wear.

Giscode: W2+, abZ-Nr. Z-157, 10-46

Degree of gloss

Matt, semigloss

Application

AQUASEAL® SMARTHOME is applied in undiluted form. It is rolled in 3 coats or is rolled once and then cross-troweled twice and once again rolled once or twice thereafter.

Special tips

Unlike conventional solvent-based hardwood-floor lacquers, AQUASEAL® SMARTHOME should be applied in rich layers, i.e. the material should not be roller-spread too thin.

Only following systems can be used as primer for AQUASEAL® SMARTHOME:

- AQUASEAL® UNISPACHTEL
- AQUASEAL® FLEXPRIMER
- AQUASEAL® EXOBLOC

Drying

At 23°C/50% rel. humidity: With one coat applied by roller or brush, surface can be sanded or walked on carefully after approx. 3-4 h. With one trowel-applied coat: Approx. 10-20 minutes. Insufficient ventilation, low temperatures, high humidity or thick coats may delay drying considerably. Do not expose to wear, cover with carpets or use care products for 8-14 days.

Consumption

Depending on floor surface and working method:

1 trowel coat as intermediate filling:
approx. 30 ml/m² resp. approx. 35 m²/l

1 roller/brush coat:
approx. 10 ml/m² resp. approx. 10 m²/l

Storage / transport

Shelf life of original unopened packing 12 months min. provided that material is transported and stored at a cool and dry place protected from freezing.

Industrially coated pre-finished hardwood floors

AQUASEAL® SMARTHOME is not suitable for recoating of pre-finished hardwood floors or cork.

Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)